Air hydraulic jack 15-30-50T

Reference : OH 5030N




Item name	Air hydraulic jack 15-30-50T
Bar code	3700461496943
Product highlight	Triple Capacity: 15, 30, and 50 metric tons
Specifications	Specifications: - Overload protection system - Equipped with a descent speed control valve for added safety - 3 stages: 15-30-50T - Long T-handle for easy positioning of the jack under the vehicle - 3-position handle: 90°, 45°, 0° with metal locking mechanism - Min. height: without extensions 150 mm / with extensions 270 mm - Max. height: without extensions 312 mm / with extensions 387 mm - Length: 858 mm - Width: 275 mm - Treated piston for high strength - Extensions: 45–75 mm - Supply pressure: 9–12 bar - Weight: 56 kg
Applications	Applications: Trucks, trailers, buses, agricultural machinery, and construction equipment.
Warranty period	2 years
Length (mm)	825 mm

Width	282 mm
Product weight (kg)	56 kg
Max. height	302 mm
Min. height	150 mm
Jack type	Hydropneumatic
Maximum load (T)	50 T
Tariff code	Tariff Normal (TN)
Composition of nomenclature	1 x OH 5030-1 - Air hydraulic jack 15-30-50T 1 x OH 5030-2 - Air hydraulic jack handle 15-30-50T
Warranty Procedure	NO

Quick tip videos

Cliquez sur l'opération qui vous intéresse pour voir la **vidéo**:





REMPLACEMENT DU BLOC COMMANDE

***Public price Exl. Tax : €1,990**

*Applicable user fees from 01/09/2026 to 31/08/2027

CLAS EQUIPEMENTS
83, chemin de la CROUZA
73800 CHIGNIN
France

Tel : +33 (0) 4 79 72 62 22
Fax :

Monday to Friday - From 8 to 12h and from 13h30 to 17h30 (16h30 on Friday)