

## LIFTING TABLE 1000kg FOR EV BATTERY AND HEAVY ORGANS

Reference : OH 1301



<b>Item name</b>	LIFTING TABLE 1000kg FOR EV BATTERY AND HEAVY ORGANS
<b>EAN code</b>	3700461499470
<b>Intro</b>	<p>This table is specially designed for the removal and re-installation of heavy components with a maximum load of 1T (electric vehicle battery and/or drive train). Versatile, it will be able to adapt to all your needs thanks to its many adjustments and its optional supports on request.</p>
<b>Text</b>	<p>A hydropneumatic control allows effortless, fast and precise height control. The descent is secured by the "dead man" function which requires 2 simultaneous actions of the operator. This function will be automatically stopped in case of problem concerning the operator. The platform is fully mobile in relation to its frame and has 104 M10x1.5 drilled and tapped points, which can be used to receive various accessories (available on request).</p>
<b>Product highlight</b>	Precision and maneuverability
<b>Specifications</b>	<p>Specifications:</p> <ul style="list-style-type: none"><li>- length: 1680mm</li><li>- width: 780mm</li><li>- height: 1000mm</li><li>- minimum tray height: 725mm</li><li>- maximum height of the tray: 1995mm</li><li>- maximum shelf length: 1560mm</li><li>- minimum tray length: 1340mm</li><li>- climb time: +/-60s</li></ul>

- descent time: +/-20s
- 4 swivel braking wheels: 130mm
- 4 handles place around the table for optimal ease of use when adjusting the load to the stand.
- weight: 385kg

#### Adjustments :

- the tray is deployed in three lockable positions for a max. area of 1560mmx730mm. It is tapped M10x1.5 to receive different accessories (available on request).
- table flatness is adjustable in 2 points for high positioning accuracy (tilt degree +/- 20%)
- the tray is movable in translation and swivelable for greater precision during the element support.

#### Contents

##### Composition:

Delivered in 4 packages to be mounted

- package n°1 : mounted lifting table
- package n°2 : 4 swivel wheels, 4 tray handles, 2 control cables for descent release, 1 pump support, screws and assembly instructions.
- package n°3 : handle frame and screws
- package n°4 : pump, hydraulic hose and seals.

#### Options

##### Option:

- screwable supports (ex: CO1160)

#### Warranty period

2 years

#### Length

1,680.00 mm

#### Width

785.00 mm

#### Height

1,000.00 mm

#### Product weight

385.00 kg

#### Max. height

1,995.00 mm

#### Min. height

725.00 mm

#### Maximum load (T)


1.00 T

#### Tariff code

Tariff Equipment (TE)

#### Warranty Procedure

DIAGNOSTIC



CLAS EQUIPEMENTS  
83, chemin de la CROUZA  
73800 CHIGNIN  
France

Tel : +33 (0) 4 79 72 62 22  
Fax :

Monday to Friday - From 8 to  
12h30 and from 14h to 17h30  
(16h30 on Friday)