Smoke leak detector

Reference : AC 0410



Item name	Smoke leak detector
Bar code	3700461400940
Text	Thanks to its compact size, this machine is easy to transport, enabling it to be used throughout the workshop. Its integrated compressor eliminates the need for an air supply. Compatible with the majority of the vehicle fleet, and connected to the battery terminals, it enables rapid diagnosis of the vehicle's closed circuits (turbo, exhaust, cooling, etc.). To detect micro-leaks in : - vacuum - exhaust - turbo insulation - oil pan - intake - cooling This device drastically reduces leak detection time by releasing opaque, fine smoke that can be instantly identified even on the smallest leaks. No risk to user or vehicle.
Product highlight	Integrated compressor Leakage rate reading

Specifications

	Specifications: - Power supply: 12V - Output pressure: 1.2 bar for turbo systems / 0.05 bar for exhaust systems - Flow rate: 8 L/min - Smoke adjustment - Operating mode: air only or smoke - Pressure gauge - Oil capacity: 50 ml - 250 ml mineral oil (included) - Comes with accessories - Test fluid 250 ml = 35 hours of use - Weight: 6 kg - Dimensions: 260 x 210 x 230 mm
Contents	Contents: - Main unit - Accessory kit - Adapter cone - Power cord - Exhaust hose - Funnel - Adjustable universal suction bag - replacement rubber gasket for the bag - test fluid (250 ml) - oil filler cap adapter (for most BMW vehicles) - smoke diffuser - accessory kit for the EVAP system (evaporative emissions control system) - set of sealing caps
Warranty period	2 years
Voltage	12V
More	Use oiler
Product weight (kg)	6 kg
Capacity (ml)	50 ml
Capacity (l)	0.05 l
Tariff code	Tariff Normal (TN)
Warranty Procedure	DIAGNOSTIC
Customer benefit	Low-pressure management protects components. Product quality for regular/intensive use.



CLAS EQUIPEMENTS
83, chemin de la CROUZA
73800 CHIGNIN
France

Tel : +33 (0) 4 79 72 62 22
Fax :

Monday to Friday - From 8 to 12h and from 13h30 to 17h30 (16h30 on Friday)