

PREMIUM INSULATED PHONE PIERS WITH LONG STRAIGHT HALF ROUND BEAKS

Reference : OE 0526



Item name	PREMIUM INSULATED PHONE PIERS WITH LONG STRAIGHT HALF ROUND BEAKS
Bar code	3700461406997
Introduction	<p>Allows easy bending of electrical wires. Suitable for work requiring precision gripping and cutting. Nozzle length adapted to reach hard-to-reach parts. Chrome-plated finish for high corrosion protection thanks to a succession of 5 baths. Induction treatment of cutting edge forging for long jaw life. Insulating reinforcements at arm ends to protect against impact. Beak gripping surface with soft ridges (prevents cable damage).</p>
Text	<p>Pliers with long, straight, half-round tips. Insulated 1000V.</p> <p>The 2 insulating layers are color-coded to allow visual inspection of the entire tool for proper use in an electrical environment, as recommended by UTE18-510 and IEC 60900. WHEN THE ORANGE LAYER IS DAMAGED AND THE RED LAYER IS VISIBLE = DANGER.</p> <ul style="list-style-type: none">- The thickness of the insulating layers is determined by the weight of the tools to ensure optimum resistance.- Tools are designed to withstand extreme temperatures from -20 to +70°C.- Each tool is tested to 10,000V AC and approved to 1000V AC for use on low-voltage networks.

- Several checks at every stage of production, in addition to IEC 60900 standard checks.

Product highlight Safety: wear indicator
Lifetime warranty

Specifications Specifications :
- standard: NF EN 60900 / CEI 60900 / NF ISO 5743 / NF ISO 5744 / NF ISO 5745
- cutting edge hardness: 60HRC
- cutting edge: axial cut
- inside jaws: serrated
- cutting capacity: 160 kg/mm² medium-hard steel wire: Ø1.6mm
- high-performance steel: chrome vanadium

Warranty period lifetime

Voltage 1000V

Length (mm) 205 mm

Product weight (kg) 240 kg

Tariff code Tariff Normal (TN)

Warranty Procedure EASY



CLAS EQUIPEMENTS
83, chemin de la CROUZA
73800 CHIGNIN
France

Tel : +33 (0) 4 79 72 62 22
Fax :

Monday to Friday - From 8 to 12h
and from 13h30 to 17h30 (16h30 on
Friday)