

## EXHAUST GAS ON ROLLER MOTORCYCLE 15m Ø75mm HIGH PRESSURE 400V

Reference: AG 0006



Item name EXHAUST GAS ON ROLLER MOTORCYCLE 15m Ø75mm HIGH PRESSURE 400V

**EAN code** 3701555300955

**Intro** Specially designed for exhaust extraction in motorcycle workshops.

Text This mechanical spring reel complete with exhaust blower can be installed on the ceiling or wall, always maintaining the same performance. The equipment allows you to work in a healthy environment without inhalation of exhaust gases and in compliance with work safety standards.

Hose: anti-crushing structure, maintains flexibility over time thanks to the robust nylon spiral with a very tight pitch. This feature prevents the hose from stretching during pulling and from collapsing in high stress situations. Its smooth design on the inside guarantees maximum suction efficiency in m3.

Directly coupled electric motor, statically and dynamically balanced impeller to limit friction, vibration and reduce energy consumption. Inlet and outlet flanges are sized for optimum suction capacity. Support feet for wall or ceiling mounting are included.

## **Specifications**

## Specifications:

- galvanized steel structure
- epoxy paint (grey RAL 7040)
- 15m of pipe Ø75mm (-40 $^{\circ}$  to +200 $^{\circ}$ ) in high temperature EPDM vulcanized fabric on both sides
- delivery: Ø160mm
- power supply: 400V Tri

- engine power: 0.5hp, 0.37KW, 50HZ, 1.0A

- max flow: 350m3/h - noise level: 66dB

- thermal protection switch

- reel equipped with a ratchet, an end stop with anti-skid system

- exhaust nozzle equipped with an anti-intrusion grid, a vice grip, a gas suction shutter

and an access for the opacimeter probe

- weight: 43kg

Many options available, please contact us.

Warranty period 2 years

Vehicle type Moto

**Decibel level** 66.00 dB

**Tension** 400V

Cable length 15.00 m

**Product weight** 43.00 kg

**Diameter** 75.00 mm

Air flow rate 350

Tariff code Tariff Equipment (TE)

Type of gas Fixed

extraction system

**DPF** compatible NO

Hose length (m) 12m

Hose diameter (mm) 75mm

200°C Max. hose

temperature (°C)





