Exhaust gas on roller 10m Ø100mm 240V

Reference : AG 0007



Item name	Exhaust gas on roller 10m Ø100mm 240V
Bar code	3701555300962
Introduction	Specially designed for exhaust extraction in light vehicle workshops.
Text	This spring-loaded mechanical winder, complete with extraction fan, can be installed on the ceiling or wall, while maintaining the same performance. The equipment allows you to work in a healthy environment, without inhaling exhaust fumes and in compliance with workplace safety standards. Hose: anti-crushing structure, maintains flexibility over time thanks to the robust nylon spiral with a very tight pitch. This feature prevents the hose from stretching when pulled, and from crushing in high-stress situations. Its smooth interior design guarantees maximum suction efficiency in m3. Directly coupled electric Engine, statically and dynamically balanced impeller to limit friction and vibration and reduce energy consumption. Inlet and outlet flanges dimensioned for optimum suction capacity. Support feet for wall or ceiling mounting are included.
Specifications	Specifications: - Galvanized steel frame - Epoxy coating (gray RAL 7040) - 10 m of Ø100 mm hose (-40° to +200°) made of high-temperature vulcanized EPDM fabric on both sides. - discharge: Ø 125 mm - power supply: 240 V single-phase

- motor power: 0.5 cv, 0.35 kW, 50 Hz, 1.7 A
- maximum airflow: 450 m³/h
- Noise level: 66 dB
- Thermal protection switch
- Reel equipped with a ratchet, an end-of-travel stop with an anti-slip system
- Exhaust nozzle equipped with an anti-intrusion grille, a clamp, a gas intake shut-off flap, and an access point for the opacimeter probe
- Weight: 43 kg

Many options available—please contact us.

Warranty period	2 years
Vehicle type	LV
Decibel level	66 dB
Voltage	240V
Product weight (kg)	43 kg
Diameter (mm)	100 mm
Air flow rate	450
Tariff code	Tariff Equipment (TE)
Type of gas extraction system	Fixed
DPF compatible	NO
Hose length (m)	10m
Hose diameter (mm)	100mm
Max. hose temperature (°C)	200°C
Customer benefit	Hose connection to reel via ABS gooseneck, guarantees no deformation, no loss of suction efficiency.



***Public price Excl. Tax : €3,319**

*Applicable user fees from 01/09/2026 to 31/08/2027

CLAS EQUIPEMENTS
83, chemin de la CROUZA
73800 CHIGNIN
France

Tel : +33 (0) 4 79 72 62 22
Fax :

Monday to Friday - From 8 to 12h and from 13h30 to 17h30 (16h30 on Friday)