

## Gas suction on reel 15m Ø100mm 240V

Reference : AG 0009



**Item name** Gas suction on reel 15m Ø100mm 240V

**Bar code** 3701555300986

**Introduction** Specially designed for exhaust extraction in light vehicle workshops.

**Text** This spring-loaded mechanical winder, complete with extraction fan, can be installed on the ceiling or wall, while maintaining the same performance. The equipment allows you to work in a healthy environment, without inhaling exhaust fumes and in compliance with workplace safety standards.

Hose: anti-crushing structure, maintains flexibility over time thanks to the robust nylon spiral with a very tight pitch. This feature prevents the hose from stretching when pulled, and from crushing in high-stress situations. Its smooth interior design guarantees maximum suction efficiency in m<sup>3</sup>.

Directly coupled electric Engine, statically and dynamically balanced impeller to limit friction and vibration and reduce energy consumption. Inlet and outlet flanges dimensioned for optimum suction capacity. Support feet for wall or ceiling mounting are included.

### Specifications

Specifications :

- galvanized steel structure
- epoxy paint (grey RAL 7040)
- 15m Ø100mm pipe (-40° to +200°) in high-temperature EPDM vulcanized fabric on both sides.
- discharge: Ø125mm
- power supply: 240V Mono

- motor power: 0.5hp, 0.35KW, 50HZ, 1.7A
- max flow: 450m3/h
- noise level: 66dB
- thermal protection switch
- reels equipped with ratchet, end-of-stroke stop and anti-slip system
- exhaust bits fitted with anti-intrusion grid, vice grip, gas suction shut-off flap and access for opacimeter probe
- weight: 43kg

Numerous options available on request.

<b>Warranty period</b>	2 years
<b>Vehicle type</b>	LV
<b>Decibel level</b>	66 dB
<b>Voltage</b>	240V
<b>Product weight (kg)</b>	43 kg
<b>Diameter (mm)</b>	100 mm
<b>Air flow rate</b>	450
<b>Tariff code</b>	Tariff Equipment (TE)
<b>Type of gas extraction system</b>	Fixed
<b>DPF compatible</b>	NO
<b>Hose length (m)</b>	12m
<b>Hose diameter (mm)</b>	100mm
<b>Max. hose temperature (°C)</b>	200°C



CLAS EQUIPEMENTS  
83, chemin de la CROUZA  
73800 CHIGNIN  
France

Tel : +33 (0) 4 79 72 62 22  
Fax :

Monday to Friday - From 8 to 12h  
and from 13h30 to 17h30 (16h30 on  
Friday)