

EXHAUST GAS ON ROLLER 15m Ø100mm 400V

Reference: AG 0010



Item name EXHAUST GAS ON ROLLER 15m Ø100mm 400V

EAN code 3701555300993

Intro Specially designed for exhaust gas suction for LV workshops.

Text This mechanical spring reel complete with exhaust blower can be installed on the ceiling or wall, always maintaining the same performance. The equipment allows you to work in

a healthy environment without inhalation of exhaust gases and in compliance with work

safety standards.

Hose: anti-crushing structure, maintains flexibility over time thanks to the robust nylon spiral with a very tight pitch. This feature prevents the hose from stretching during pulling and from collapsing in high stress situations. Its smooth design on the inside

guarantees maximum suction efficiency in m3.

Directly coupled electric motor, statically and dynamically balanced impeller to limit friction, vibration and reduce energy consumption. Inlet and outlet flanges are sized for optimum suction capacity. Support feet for wall or ceiling mounting are included.

Specifications

Specifications:

- galvanized steel structure
- epoxy paint (grey RAL 7040)
- 15m of pipe Ø100mm (-40° to +200°) in high temperature EPDM vulcanized fabric on both sides
- delivery: Ø125mm
- power supply: 400V Tri
- engine power: 0.5hp, 0.37KW, 50HZ, 1.0A

max flow: 450m3/hnoise level: 66dB

- thermal protection switch

- reel equipped with a ratchet, an end stop with anti-skid system

Tel: +33 (0) 4 79 72 62 22

Fax:

Monday to Friday - From 8 to

12h30 and from 14h to 17h30

(16h30 on Friday)

- exhaust nozzle equipped with an anti-intrusion grid, a vice grip, a gas suction shutter

and an access for the opacimeter probe

- weight: 43kg

Many options available, please contact us.

Warranty period 2 years

Vehicle type LV

Decibel level 66.00 dB

Tension 400V

Product weight 43.00 kg

Diameter 100.00 mm

Air flow rate 450

Tariff code Tariff Equipment (TE)

Type of gas Fixed

extraction system

DPF compatible NO

Hose length (m) 12m

Hose diameter (mm) 100mm

Max. hose 200°C

temperature (°C)







