Exhaust gas on roll heavy weights 10m Ø150mm 400V

Reference : AG 0015



Item name	Exhaust gas on roll heavy weights 10m Ø150mm 400V
Bar code	3701555301044
Introduction	Specially designed for exhaust extraction in truck workshops.
Text	This mechanical spring-loaded reel, complete with an exhaust fan, can be installed on the ceiling or wall while maintaining the same performance. The equipment performs exhaust gas extraction in compliance with workplace safety standards. Hose: crush-resistant construction; maintains flexibility over time thanks to the sturdy nylon spiral with a very tight pitch. This feature prevents the hose from stretching when pulled and from being crushed under heavy loads. Its smooth interior design ensures maximum extraction efficiency in cubic meters. Directly coupled electric motor with a statically and dynamically balanced impeller to minimize friction and vibration. The inlet and outlet flanges are sized for optimal suction capacity. Mounting brackets for wall or ceiling installation are included.
Specifications	Specifications: - Galvanized steel frame - Epoxy paint (gray RAL 7040) - 10 m of Ø150 mm hose (-40° to +200°) made of high-temperature vulcanized EPDM fabric on both sides - discharge: Ø 160 mm - Power supply: 400 Tri - Engine power: 1.0 CV, 0.75 kW, 50 Hz, 1.7 A

- Maximum flow rate: 1,000 m³/h
- Noise level: 68 dB
- Thermal protection switch
- Metal flanges
- Reel equipped with a ratchet, an end-of-travel stop with an anti-slip system
- Exhaust system nozzle equipped with an intrusion-proof grille, a clamp, a gas intake shut-off flap, and access for the opacimeter probe
- Weight: 73 kg

Many options available—please contact us.

Warranty period	2 years
Vehicle type	HGV
Decibel level	68 dB
Voltage	400V
Product weight (kg)	73 kg
Diameter (mm)	150 mm
Air flow rate	1000
Tariff code	Tariff Equipment (TE)
Type of gas extraction system	Fixed
DPF compatible	NO
Hose length (m)	10m
Hose diameter (mm)	150mm
Max. hose temperature (°C)	200°C
Customer benefit	Hose connection to reel via ABS gooseneck, guarantees no deformation, no loss of suction efficiency.



CLAS EQUIPEMENTS
83, chemin de la CROUZA
73800 CHIGNIN
France

Tel : +33 (0) 4 79 72 62 22
Fax :

Monday to Friday - From 8 to 12h and from 13h30 to 17h30 (16h30 on Friday)