

EXHAUST GAS ON ROLL 15m Ø150mm 400V

Reference : AG 0018



Item name	EXHAUST GAS ON ROLL 15m Ø150mm 400V
Bar code	3701555301075
Introduction	Specially designed for exhaust extraction in light vehicle workshops.
Text	<p>This spring-loaded mechanical winder, complete with extraction fan, can be installed on the ceiling or wall, while maintaining the same performance. The equipment allows you to work in a healthy environment, without inhaling exhaust fumes and in compliance with workplace safety standards.</p> <p>Hose: anti-crushing structure, maintains flexibility over time thanks to the robust nylon spiral with a very tight pitch. This feature prevents the hose from stretching when pulled, and from crushing in high-stress situations. Its smooth interior design guarantees maximum suction efficiency in m³.</p> <p>Directly coupled electric Engine, statically and dynamically balanced impeller to limit friction and vibration and reduce energy consumption. Inlet and outlet flanges dimensioned for optimum suction capacity. Support feet for wall or ceiling mounting are included.</p>
Product highlight	Premium exhaust Nozzle
Specifications	<p>Specifications :</p> <ul style="list-style-type: none">- galvanized steel structure- epoxy paint (grey RAL 7040)- 15m Ø150mm pipe (-40° to +200°) in high-temperature EPDM vulcanized fabric on both sides.- discharge: Ø160mm

- power supply: 400 Tri
- Engine power: 1.0hp, 0.75KW, 50HZ, 1.7A
- max flow: 1000m3/h
- noise level: 68dB
- thermally protected switch
- reel equipped with ratchet, end-of-stroke stop and anti-slip system
- exhaust nozzle equipped with anti-intrusion grid, manual clamp, gas suction shut-off flap and access for opacimeter probe
- weight: 73kg

Numerous options available on request.

Warranty period 2 years

Vehicle type LV

Decibel level 68 dB

Voltage 400V

Product weight (kg) 73 kg

Diameter (mm) 150 mm

Air flow rate 1000

Tariff code Tariff Equipment (TE)

Type of gas extraction system Fixed

DPF compatible NO

Hose length (m) 12m

Hose diameter (mm) 150mm

Max. hose temperature (°C) 200°C



CLAS EQUIPEMENTS
83, chemin de la CROUZA
73800 CHIGNIN
France

Tel : +33 (0) 4 79 72 62 22
Fax :

Monday to Friday - From 8 to 12h
and from 13h30 to 17h30 (16h30 on Friday)