

SINGLE EXTRACTOR GROUP 5m Ø100mm 400V TRIPHASE

Reference : AG 0020



Item name SINGLE EXTRACTOR GROUP 5m Ø100mm 400V TRIPHASE

EAN code 3701555301099

Intro Specially designed for exhaust gas suction for LV workshops.

Text This extractor is the easiest installation kit to install on a wall or on the front.
The equipment allows to work in a healthy environment without inhalation of exhaust gases and in compliance with the safety standards at work.

Product highlight Easy to install

Specifications Specifications:

- galvanized steel structure
- electric motor, statically and dynamically balanced wheel, delivered with wall bracket and rubber funnel.
- 5m of Ø100mm hose (-40° to +200°) made of high temperature EPDM vulcanized fabric on both sides. Completely anti-crushing structure, smooth inside and maintains flexibility over time thanks to the strong nylon spiral with a very tight pitch. This feature prevents the hose from stretching during pulling and from crushing in high stress situations.
- delivery: Ø 125mm
- power supply: 400V Tri
- motor power: 0,5cv, 0,37KW, 50HZ, 1.0A
- max flow: 450m³/h
- noise level: 66dB
- thermal protection switch

- rubber exhaust nozzle with watertight valve included in the body of the product, anti-intrusion network, clamp for fixing to the exhaust

Many options available, please consult us.

| | |
|--------------------------------------|-----------------------|
| Warranty period | 2 years |
| Vehicle type | LV |
| Decibel level | 66.00 dB |
| Tension | 400V |
| Diameter | 100.00 mm |
| Air flow rate | 450 |
| Tariff code | Tariff Equipment (TE) |
| Type of gas extraction system | Fixed |
| DPF compatible | NO |
| Hose length (m) | 5m |
| Hose diameter (mm) | 100mm |
| Max. hose temperature (°C) | 200°C |



CLAS EQUIPEMENTS
83, chemin de la CROUZA
73800 CHIGNIN
France

Tel : +33 (0) 4 79 72 62 22
Fax :

Monday to Friday - From 8 to
12h30 and from 14h to 17h30
(16h30 on Friday)