

Gas suction unit double descent 2x5m Ø100mm 240V

Reference : AG 0021



Item name	Gas suction unit double descent 2x5m Ø100mm 240V
Bar code	3701555301105
Introduction	Specially designed for exhaust extraction in light vehicle workshops. Suitable for wall or roof extraction, depending on accessories.
Text	The equipment enables you to work in a healthy environment, without inhaling exhaust fumes and in compliance with workplace safety standards.
Product highlight	Easy to install
Specifications	Specifications : <ul style="list-style-type: none">- painted steel structure ral 7040- Ø100mm hose (-40° to +200°) in high-temperature EPDM vulcanized fabric. hose structure is completely anti-crushing, maintains flexibility over time, and retains suction characteristics- discharge: Ø125mm- power supply: 240V Mono- motor power: 1hp, 0.75KW, 50HZ, 2.9A- max flow: 450m³/h- noise level: 66dB- thermal protection switch- rubber nozzles, 160mm opening, with fixing clamp and anti-intrusion isolation valve
Warranty period	2 years

Vehicle type	LV
Decibel level	66 dB
Voltage	240V
Diameter (mm)	100 mm
Air flow rate	2X450
Tariff code	Tariff Equipment (TE)
Type of gas extraction system	Fixed
DPF compatible	NO
Hose length (m)	2 x 5m
Hose diameter (mm)	100mm
Max. hose temperature (°C)	200°C

2
WARRANTY



TE

TENSION240V.jpg

***Public price Exl. Tax : €2,469**

*Applicable user fees from 01/09/2025 to 31/08/2026

CLAS EQUIPEMENTS
83, chemin de la CROUZA
73800 CHIGNIN
France

Tel : +33 (0) 4 79 72 62 22
Fax :

Monday to Friday - From 8 to 12h
and from 13h30 to 17h30 (16h30 on
Friday)