
2 columns asymetric post lift with basement 230V 4T

Reference : PE 2000M



Item name	2 columns asymetric post lift with basement 230V 4T
Bar code	3701555306896
Introduction	Specially designed for screeds that don't meet the minimum thickness requirement of 200mm, or with slight flatness problems.
Text	Electro-hydraulic post lift. Push cylinder on cart, chainless. Multiple lifting capacities thanks to telescopic arms in asymmetrical version (short front 3 stages from 560mm to 995mm - long rear 2 stages from 660 to 1210mm). Cylinder and cable protection strip included on each column.
Product highlight	Thin slab
Specifications	Specifications : - lifting height: 126-1890mm - lifting time: +/- 40s - lowering time: +/- 40s - drive power: 2.2kW - drive voltage: (3 ~) 400/50 V/Hz - concrete strength/quality: 150mm-C20/25 - adjustable screw pads, stroke 55mm - electromagnetic release of safety catches - overload and hose rupture protection - system synchronization: by cable - protective strip for cylinder, chain and cables included on each column

	- made in Europe - Epoxy paint
Options	Options : - PE0007: Mercedes/Iveco 105-135mm extension sets
Advice	Installation et mise en service, nous consulter. (ne pas installer sur une dalle d'une épaisseur à 150mm) Dans le cadre de la garantie, l'installation et la mise en service doivent être effectuées par un professionnel. Frais de transport non inclus.
Warranty period	2 years
Power	2200W
Voltage	240V
Product weight (kg)	800 kg
Maximum load (T)	4 T
Tariff code	Tariff Equipment (TE)
Composition of nomenclature	1 x PE 2000M-1 - 2 columns asymetric post lift with basement 230V 4T pack. 1/3 1 x PE 2000M-2 - 2 columns asymetric post lift with basement 230V 4T pack. 2/3 1 x PE 2000M-3 - 2 columns asymetric post lift with basement 230V 4T pack. 3/3



CLAS EQUIPEMENTS
83, chemin de la CROUZA
73800 CHIGNIN
France

Tel : +33 (0) 4 79 72 62 22
Fax :

Monday to Friday - From 8 to 12h and from 13h30 to 17h30 (16h30 on Friday)