

2 columns asymmetric post lift with basement 400V 4T

Reference : PE 2000T



Item name	2 columns asymmetric post lift with basement 400V 4T
Bar code	3701555306902
Introduction	Specially designed for screeds that don't meet the minimum thickness requirement of 200mm, or with slight flatness problems.
Text	Electro-hydraulic post lift. Push cylinder on cart, chainless. Multiple lifting capacities thanks to telescopic arms in asymmetrical version (short front 3 stages from 560mm to 995mm - long rear 2 stages from 660 to 1210mm). Cylinder and cable protection strip included on each column.
Product highlight	Thin slab
Specifications	Specifications : <ul style="list-style-type: none">- lifting height: 126-1890mm- lifting time: +/- 40s- lowering time: +/- 40s- drive power: 2.2kW- drive voltage: (3 ~) 400/50 V/Hz- concrete strength/quality: 150mm-C20/25- screw-adjustable pads, stroke 55mm- electromagnetic release of safety catches- overload and hose rupture protection- system synchronization: by cable- protective strip for cylinder, chain and cables included on each column

- made in Europe
- Epoxy paint

Options

Options :
- PE0007 : jeux de rehausses Mercedes / Iveco 105-135mm

Advice

Consult us for installation and commissioning.
Do not install on a slab less than 150mm thick.
For warranty purposes, installation and commissioning must be carried out by a professional.
Shipping costs excluded.

Warranty period 2 years

Power 2200W

Voltage 400V

Product weight (kg) 800 kg

Maximum load (T) 4 T

Tariff code Tariff Equipment (TE)

Composition of nomenclature 1 x PE 2000T-2 - 2 columns asymmetric post lift with basement 400V 4T pack. 2/3
1 x PE 2000T-3 - 2 columns asymmetric post lift with basement 400V 4T pack. 3/3
1 x PE 2000T-1 - 2 columns asymmetric post lift with basement 400V 4T pack. 1/3



CLAS EQUIPEMENTS
83, chemin de la CROUZA
73800 CHIGNIN
France

Tel : +33 (0) 4 79 72 62 22
Fax :

Monday to Friday - From 8 to 12h
and from 13h30 to 17h30 (16h30 on
Friday)