

2 COLUMNS ASYMETRIC POST LIFT WITH BASEMENT 400V 4T

Reference : PE 2000T



Item name	2 COLUMNS ASYMETRIC POST LIFT WITH BASEMENT 400V 4T
EAN code	3701555306902
Intro	Specially designed for screeds that do not meet the minimum thickness requirements of 200mm, or have a slight flatness problem.
Text	Electro-hydraulic post lift. Push cylinder on cart, without chain. Multiple lifting capacities thanks to the telescopic arms in asymmetrical version (short front 3 stages from 560mm to 995mm - long rear 2 stages from 660 to 1210mm). Cylinder and cable protection strip included on each column.
Product highlight	Low thickness slab
Specifications	Specifications: - lifting height: 126-1890mm - lifting time: +/- 40s - lowering time: +/- 40s - drive power: 2.2 kW - electrical voltage of the drive: (3 ~) 400/50 V/Hz - adjustable pads on 55mm stroke screw - electromagnetic unlocking of the safety notches - overload safety and hose rupture - bevelled columns for large door openings - synchronization system by cable - made in Europe

	- Epoxy painting
Options	Options : - PE0007 : jeux de rehausses Mercedes / Iveco 105-135mm
Advice	Consult us for installation and commissioning. Do not install on a slab less than 150mm thick. For warranty purposes, installation and commissioning must be carried out by a professional. Shipping costs excluded.
Warranty period	2 years
Power	2200W
Tension	400V
Product weight	800.00 kg
Maximum load (T)	4.00 T
Tariff code	Tariff Equipment (TE)
Composition of nomenclature VARRANTY 2200 400V	1 x PE 2000T-2 - 2 COLUMNS ASYMETRIC POST LIFT WITH BASEMENT 400V 4T PACK. 2/3 1 x PE 2000T-3 - 2 COLUMNS ASYMETRIC POST LIFT WITH BASEMENT 400V 4T PACK. 3/3 1 x PE 2000T-1 - 2 COLUMNS ASYMETRIC POST LIFT WITH BASEMENT 400V 4T PACK. 1/3

*Public price Exl. Tax : €4,990.00

*Applicable user fees from 01/09/2023 to 31/08/2024

CLAS EQUIPEMENTS 83, chemin de la CROUZA 73800 CHIGNIN France Tel : +33 (0) 4 79 72 62 22 Fax : Monday to Friday - From 8 to 12h30 and from 14h to 17h30 (16h30 on Friday)