

Mobile scissor lift dual cylinder low raise 400V 3T

Reference : PE 6000T



Item name	Mobile scissor lift dual cylinder low raise 400V 3T
Bar code	3701555307091
Introduction	Particularly suited to paint, bodywork, brake and tire service activities.
Text	Easy access: 105mm lowered floor passage, lockable access ramps to extend platforms. Push-button up/down control on control box. Working comfort: easy to move thanks to its set of 3 removable wheels and its traction handle.
Product highlight	Mobile
Specifications	Specifications : <ul style="list-style-type: none">- lifting height: 105-960mm- lifting time: +/- 20s- lowering time: +/- 20s- track width/length: 530/1450-2036mm- system synchronization: photo cell- drive power: 2.2kW- drive voltage: (3 ~) 400/50 V/Hz- scissor control: dual hydraulic master-slave system- full power lift at lowest point 105mm.- maximum safety: double hydraulic safety system (no mechanical detent or compressed air)- emergency lowering system in case of power failure- CE-standard anti-crushing intermediate stop and audible signal

- European origin

Advice

Installation et mise en service, nous consulter.

Dans le cadre de la garantie, l'installation et la mise en service doivent être effectuées par un professionnel.

Frais de transport non inclus.

Warranty period 2 years

Power 2200W

Voltage 400V

Product weight (kg) 540 kg

Maximum load (T) 3 T

Tariff code Tariff Equipment (TE)

Composition of nomenclature 1 x PE 6000T-1 - Mobile scissor lift dual cylinder low raise 400V 3T pack. 1/3
1 x PE 6000T-2 - Mobile scissor lift dual cylinder low raise 400V 3T pack. 2/3
1 x PE 6000T-3 - Mobile scissor lift dual cylinder low raise 400V 3T pack. 3/3



CLAS EQUIPEMENTS
83, chemin de la CROUZA
73800 CHIGNIN
France

Tel : +33 (0) 4 79 72 62 22
Fax :

Monday to Friday - From 8 to 12h
and from 13h30 to 17h30 (16h30 on
Friday)