

Double scissor lift double jack 230V 3T

Reference : PE 6001M



Item name	Double scissor lift double jack 230V 3T
Bar code	3701555307121
Introduction	Particularly suited to paint, bodywork, brake and tire service activities. Choice of installation: free-standing or built-in.
Text	Easy access: 100mm lowered floor passage, lockable access ramps to extend platforms. Up/down control via push-buttons on control console. Full power lift at lowest point 100mm. Working comfort: scissor control by double hydraulic master-slave system; synchronization control by photocell.
Specifications	Specifications : <ul style="list-style-type: none">- lifting height: 100-1950mm- lifting time: +/- 40s- lowering time: +/- 35s- track width/length: 710/1733-2090mm- system synchronization: photo cell- floor width/length required for installation: 2090/2160mm- drive power: 2.2kW- drive voltage: (3 ~) 400/50 V/Hz- concrete strength/quality: 200mm-C20/25- maximum safety: double hydraulic safety system (without mechanical detent or compressed air), emergency lowering system in the event of power failure, CE-standard anti-crushing intermediate stop and audible signal

- made in Europe

Advice

Installation et mise en service, nous consulter.

Dans le cadre de la garantie, l'installation et la mise en service doivent être effectuées par un professionnel.

Frais de transport non inclus.

Warranty period 2 years

Power 2200W

Voltage 240V

Product weight (kg) 840 kg

Maximum load (T) 3 T

Tariff code Tariff Equipment (TE)

Composition of 1 x PE 6001M-1 - Double scissor lift double jack 230V 3T package 1/2

nomenclature 1 x PE 6001M-2 - Double scissor lift double jack 230V 3T package 2/2



2200
W



TE

TENSION240V.jpg

CLAS EQUIPEMENTS
83, chemin de la CROUZA
73800 CHIGNIN
France

Tel : +33 (0) 4 79 72 62 22
Fax :

Monday to Friday - From 8 to 12h
and from 13h30 to 17h30 (16h30 on
Friday)