

DOUBLE SCISSOR LIFT DUAL CYLINDER 400V 3T

Reference: PE 6001T



Item name DOUBLE SCISSOR LIFT DUAL CYLINDER 400V 3T

EAN code 3701555307138

Intro Especially adapted to painting, bodywork and brake and tyre service activities.

Installation possibilities: floor-standing or floor built-in.

Text Ease of access: 100mm high lowered floor passage, lockable access ramps for extended

lifting platforms

Up and down control by push buttons on control console

Powerful lift: Extended mechanical tilt lever system, for full power lift at the lowest point

100mm

Working comfort: scissors control by double hydraulic master-slave system;

synchronization control by photocell.

Specifications Specifications:

- lifting height: 100-1950mm

- lifting time : +/- 40s - lowering time: +/- 35s

- width/length of tracks: 650/1420-2000mm

- system synchronization: photo cell

- width/length of floor required for installation: 2000/2030mm

- drive power: 2.2kW

- drive voltage: (3 ~) 400/50 V/Hz

- concrete strength/quality: 200mm-C20/25

- Maximum safety: double hydraulic safety system (without mechanical lock and

compressed air), emergency lowering system in case of power failure, anti-crushing

intermediate stop according to CE standards and sound signal

- made in Europe

Advice Installation et mise en service, nous consulter.

Dans le cadre de la garantie, l'installation et la mise en service doivent être effectuées par

un professionnel.

Frais de transport non inclus.

Warranty period 2 years

Power 2200W

Tension 400V

Product weight 840.00 kg

Maximum load (T) 3.00 T

Tariff code Tariff Equipment (TE)

Composition of1 x PE 6001T-1 - DOUBLE SCISSOR LIFT DUAL CYLINDER 400V 3T PACK. 1/2
1 x PE 6001T-2 - DOUBLE SCISSOR LIFT DUAL CYLINDER 400V 3T PACK. 2/2











CLAS EQUIPEMENTS 83, chemin de la CROUZA 73800 CHIGNIN France Tel: +33 (0) 4 79 72 62 22

Fax:

Monday to Friday - From 8 to 12h30 and from 14h to 17h30 (16h30 on Friday)