

DOUBLE SCISSOR LIFT DUAL CYLINDER 400V 3T

Reference : PE 6001T



Item name	DOUBLE SCISSOR LIFT DUAL CYLINDER 400V 3T
EAN code	3701555307138
Intro	Especially adapted to painting, bodywork and brake and tyre service activities. Installation possibilities: floor-standing or floor built-in.
Text	Ease of access: 100mm high lowered floor passage, lockable access ramps for extended lifting platforms Up and down control by push buttons on control console Powerful lift: Extended mechanical tilt lever system, for full power lift at the lowest point 100mm Working comfort: scissors control by double hydraulic master-slave system; synchronization control by photocell.
Specifications	 Specifications: lifting height : 100-1950mm lifting time : +/- 40s lowering time: +/- 35s width/length of tracks: 650/1420-2000mm system synchronization: photo cell width/length of floor required for installation: 2000/2030mm drive power: 2.2kW drive voltage: (3 ~) 400/50 V/Hz concrete strength/quality: 200mm-C20/25 Maximum safety: double hydraulic safety system (without mechanical lock and

Advice	 compressed air), emergency lowering system in case of power failure, anti-crushing intermediate stop according to CE standards and sound signal - made in Europe Installation et mise en service, nous consulter. Dans le cadre de la garantie, l'installation et la mise en service doivent être effectuées par un professionnel. Frais de transport non inclus.
Warranty period	2 years
Power	2200W
Tension	400V
Product weight	840.00 kg
Maximum load (T)	3.00 T
Tariff code	Tariff Equipment (TE)
Composition of nomenclature 2200 WARRANTY W 400V	1 x PE 6001T-1 - DOUBLE SCISSOR LIFT DUAL CYLINDER 400V 3T PACK. 1/2 1 x PE 6001T-2 - DOUBLE SCISSOR LIFT DUAL CYLINDER 400V 3T PACK. 2/2

*Public price Exl. Tax : €6,350.00

*Applicable user fees from 01/09/2023 to 31/08/2024

CLAS EQUIPEMENTS 83, chemin de la CROUZA 73800 CHIGNIN France Tel : +33 (0) 4 79 72 62 22 Fax : Monday to Friday - From 8 to 12h30 and from 14h to 17h30 (16h30 on Friday)