

Scissor lift dual cylinder low raise 230V 3T

Reference : PE 6002M



Item name Scissor lift dual cylinder low raise 230V 3T

Bar code 3701555307107

Introduction Particularly suited to paint, bodywork, brake and tire service activities.
Choice of installation: free-standing or built-in.

Text Easy access: 105mm lowered floor passage, lockable access ramps to extend platforms.
Up/down control via push-buttons on control box.
Working comfort: scissor control by dual hydraulic master-slave system, photocell synchronization control, adjustable ramp spacing from 700 to 900mm, suitable for microcars, suvs and utility vehicles.
Full power lift at lowest point 105mm.

Product highlight Ideal micro car

Specifications Specifications :
- lifting height: 105-960mm
- lifting time: +/- 20s
- lowering time: +/- 20s
- track width/length: 530/1450-2036mm
- system synchronization: photocell
- drive power: 2.2kw
- drive voltage: (3 ~) 400/50 V/Hz
- maximum safety: double hydraulic safety system (no mechanical detent or compressed air), emergency lowering system in the event of power failure, CE-standard anti-crushing intermediate stop and acoustic signal

- made in Europe

Advice

Installation et mise en service, nous consulter.

Dans le cadre de la garantie, l'installation et la mise en service doivent être effectuées par un professionnel.

Frais de transport non inclus.

Warranty period 2 years

Power 2200W

Voltage 240V

Product weight (kg) 610 kg

Maximum load (T) 3 T

Tariff code Tariff Equipment (TE)

Composition of nomenclature 1 x PE 6002M-1 - Scissor lift dual cylinder low raise 230V 3T pack. 1/2
1 x PE 6002M-2 - Scissor lift dual cylinder low raise 230V 3T pack. 2/2



CLAS EQUIPEMENTS
83, chemin de la CROUZA
73800 CHIGNIN
France

Tel : +33 (0) 4 79 72 62 22
Fax :

Monday to Friday - From 8 to 12h
and from 13h30 to 17h30 (16h30 on
Friday)