Scissor lift dual cylinder low raise 400V 3T

Reference : PE 6002T



Item name	Scissor lift dual cylinder low raise 400V 3T
Bar code	3701555307114
Introduction	Particularly suited to paint, bodywork, brake and tire service activities. Choice of installation: free-standing or built-in.
Text	Easy access: 105mm lowered floor passage, lockable access ramps to extend platforms. Up/down control via push-buttons on control box. Working comfort: scissor control by dual hydraulic master-slave system, photocell synchronization control, adjustable ramp spacing from 700 to 900mm, suitable for microcars, suvs and utility vehicles. Full power lift at lowest point 105mm.
Product highlight	Ideal micro car
Specifications	Specifications : - lifting height: 105-960mm - lifting time: +/- 20s - lowering time: +/- 20s - track width/length: 530/1450-2036mm - system synchronization: photocell - drive power: 2.2kw - drive voltage: (3 ~) 400/50 V/Hz - maximum safety: double hydraulic safety system (no mechanical detent or compressed air), emergency lowering system in the event of power failure, CE-standard anti-crushing intermediate stop and acoustic signal

	- made in Europe
Advice	Installation et mise en service, nous consulter. Dans le cadre de la garantie, l'installation et la mise en service doivent être effectuées par un professionnel. Frais de transport non inclus.
Warranty period	2 years
Power	2200W
Voltage	400V
Product weight (kg)	610 kg
Maximum load (T)	3 T
Tariff code	Tariff Equipment (TE)
Composition of nomenclature	1 x PE 6002T-1 - Scissor lift dual cylinder low raise 400V 3T pack. 1/2 1 x PE 6002T-2 - Scissor lift dual cylinder low raise 400V 3T pack. 2/2



CLAS EQUIPEMENTS
83, chemin de la CROUZA
73800 CHIGNIN
France

Tel : +33 (0) 4 79 72 62 22
Fax :

Monday to Friday - From 8 to 12h and from 13h30 to 17h30 (16h30 on Friday)