

Double scissor lift dual cylinder 230V 3.5T

Reference : PE 6004M



Item name	Double scissor lift dual cylinder 230V 3.5T
Bar code	3701555307145
Introduction	Particularly suited to paint, bodywork, brake and tire service activities. Choice of installation: free-standing or built-in.
Text	Easy access: 105mm lowered floor passage, lockable access ramps to extend platforms. Up/down control via push-buttons on control console. Full power lift at lowest point 105mm. Maximum comfort and safety: control by double hydraulic master-slave safety system, synchronization control by photocell (without mechanical detent or compressed air),
Specifications	Specifications : <ul style="list-style-type: none">- lifting height: 105-1950mm- lifting time: +/- 40s- lowering time: +/- 35s- track width/length: 650/1420-2000mm- system synchronization: photo cell- control console- floor width/length required for installation: 2000/2030mm- drive power: 2.2kw- drive voltage: (3 ~) 400/50 V/Hz- concrete strength/quality: 200mm-C20/25- emergency lowering system in the event of power failure, CE-compliant anti-crushing intermediate stop and audible signal

- made in Europe

Advice

Installation et mise en service, nous consulter.

Dans le cadre de la garantie, l'installation et la mise en service doivent être effectuées par un professionnel.

Frais de transport non inclus.

Warranty period 2 years

Power 2200W

Voltage 240V

Length (mm) 2,270 mm

Width 2,130 mm

Product weight (kg) 860 kg

Max. height 1,950 mm

Maximum load (T) 3.50 T

Tariff code Tariff Equipment (TE)

Composition of nomenclature 1 x PE 6004M-1 - Double scissor lift dual cylinder 230V 3.5T pack. 1/2

1 x PE 6004M-2 - Double scissor lift dual cylinder 230V 3.5T pack. 2/2



TENSION240V.jpg

CLAS EQUIPEMENTS
83, chemin de la CROUZA
73800 CHIGNIN
France

Tel : +33 (0) 4 79 72 62 22
Fax :

Monday to Friday - From 8 to 12h
and from 13h30 to 17h30 (16h30 on
Friday)