

## DOUBLE SCISSOR LIFT DUAL CYLINDER 230V 3.5T

Reference : PE 6004M



| Item name      | DOUBLE SCISSOR LIFT DUAL CYLINDER 230V 3.5T                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
|----------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| EAN code       | 3701555307145                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| Intro          | Especially adapted to painting, bodywork and brake and tyre service activities.<br>Installation possibilities: floor-standing or floor built-in.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Text           | <ul> <li>Ease of access: 105mm high lowered floor passage, lockable access ramps for extended lifting platforms.</li> <li>Up and down control by push buttons on control console.</li> <li>Powerful lift: Extended mechanical tilt lever system, for full power lift at the lowest point 105mm.</li> <li>Working comfort &amp; maximum safety: scissors control by double hydraulic safety masterslave system (without mechanical detent or compressed air) synchronization control by photocell, emergency lowering system in case of power failure, intermediate anticrushing stop to CE standards and audible signal.</li> <li>European origin.</li> </ul> |
| Specifications | Specifications:<br>- lifting height : 105-1950mm<br>- lifting time : +/- 40s<br>- lowering time: +/- 35s<br>- track width/length: 650/1420-2000mm<br>- system synchronization: photo cell<br>- control console<br>- width/length of floor required for installation: 2000/2030mm                                                                                                                                                                                                                                                                                                                                                                              |

|                                                           | <ul> <li>drive power: 2.2kw</li> <li>Drive voltage: (3 ~) 400/50V/Hz</li> <li>concrete strength/quality: 200mm-C20/25</li> <li>Emergency lowering system in case of power failure, anti-crushing intermediate stop according to CE standards and sound signal</li> <li>made in Europe</li> </ul> |
|-----------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Advice                                                    | Installation et mise en service, nous consulter.<br>Dans le cadre de la garantie, l'installation et la mise en service doivent être effectuées par<br>un professionnel.<br>Frais de transport non inclus.                                                                                        |
| Warranty period                                           | 2 years                                                                                                                                                                                                                                                                                          |
| Power                                                     | 2200W                                                                                                                                                                                                                                                                                            |
| Tension                                                   | 230V                                                                                                                                                                                                                                                                                             |
| Length                                                    | 2,270.00 mm                                                                                                                                                                                                                                                                                      |
| Width                                                     | 2,130.00 mm                                                                                                                                                                                                                                                                                      |
| Product weight                                            | 860.00 kg                                                                                                                                                                                                                                                                                        |
| Max. height                                               | 1,950.00 mm                                                                                                                                                                                                                                                                                      |
| Maximum load (T)                                          | 3.50 T                                                                                                                                                                                                                                                                                           |
| Tariff code                                               | Tariff Equipment (TE)                                                                                                                                                                                                                                                                            |
| Composition of<br>nomenclature<br>2200<br>WARRANTY W 230V | 1 x PE 6004M-1 - DOUBLE SCISSOR LIFT DUAL CYLINDER 230V 3.5T PACK. 1/2<br>1 x PE 6004M-2 - DOUBLE SCISSOR LIFT DUAL CYLINDER 230V 3.5T PACK. 2/2                                                                                                                                                 |

CLAS EQUIPEMENTS 83, chemin de la CROUZA 73800 CHIGNIN France Tel : +33 (0) 4 79 72 62 22 Fax : Monday to Friday - From 8 to 12h30 and from 14h to 17h30 (16h30 on Friday)