Double scissor lift dual cylinder 400V 3.5T

Reference : PE 6004T



Item name	Double scissor lift dual cylinder 400V 3.5T
Bar code	3701555307152
Introduction	Particularly suited to paint, bodywork, brake and tire service activities. Choice of installation: free-standing or built-in.
Text	Easy access: 105mm lowered floor passage, lockable access ramps to extend platforms. Up/down control via push-buttons on control console. Full power lift at lowest point 105mm. Maximum comfort and safety: control by double hydraulic master-slave safety system, synchronization control by photocell (without mechanical detent or compressed air),
Specifications	Specifications : - lifting height: 105-1950mm - lifting time: +/- 40s - lowering time: +/- 35s - track width/length: 650/1420-2000mm - system synchronization: photo cell - control console - floor width/length required for installation: 2000/2030mm - drive power: 2.2kw - drive voltage: (3 ~) 400/50 V/Hz - concrete strength/quality: 200mm-C20/25 - emergency lowering system in the event of power failure, CE-compliant anti-crushing intermediate stop and audible signal

	- made in Europe
Advice	Installation et mise en service, nous consulter. Dans le cadre de la garantie, l'installation et la mise en service doivent être effectuées par un professionnel. Frais de transport non inclus.
Warranty period	2 years
Power	2200W
Voltage	400V
Length (mm)	2,270 mm
Width	2,130 mm
Product weight (kg)	890 kg
Max. height	1,950 mm
Maximum load (T)	3.50 T
Tariff code	Tariff Equipment (TE)
Composition of nomenclature	1 x PE 6004T-1 - Double scissor lift dual cylinder 400V 3.5T pack. 1/2 1 x PE 6004T-2 - Double scissor lift dual cylinder 400V 3.5T pack. 2/2



CLAS EQUIPEMENTS
83, chemin de la CROUZA
73800 CHIGNIN
France

Tel : +33 (0) 4 79 72 62 22
Fax :

Monday to Friday - From 8 to 12h and from 13h30 to 17h30 (16h30 on Friday)