

## SCISSOR LIFT 5T AUXILIARY LIFT 3.5T PACK. 1/1

Reference : PE 6007T



<b>Item name</b>	SCISSOR LIFT 5T AUXILIARY LIFT 3.5T PACK. 1/1
<b>Bar code</b>	3701555308470
<b>Introduction</b>	<p>Particularly suitable for technical inspections, geometries, headlamp repair and adjustment.</p> <p>Choice of installation: free-standing or built-in for light commercial vehicles.</p>
<b>Text</b>	<p>Maximum safety: 1 thrust cylinder with secure mechanical position-holding (rack and pinion) to stabilize position. The safety device is pneumatically powered.</p>
<b>Specifications</b>	<p>Specifications :</p> <ul style="list-style-type: none"><li>- lifting height: 350-2155mm</li><li>- lifting time: +/- 65s</li><li>- lowering time: +/- 60s</li><li>- track width/length: 625/5400mm</li><li>- system synchronization: photo cell</li><li>- drive power: 2.6kw</li><li>- drive voltage: (3 ~) 400/50 V/Hz</li><li>- made in Europe</li><li>- Epoxy paint</li></ul>
<b>Contents</b>	<p>Contents :</p> <ul style="list-style-type: none"><li>- shifting plates</li><li>- pivoting platform slots</li><li>- auxiliary lift 3500 kg, lift height 425mm with ramp extension L: 1430mm to 2050mm</li><li>- guide rails for lifting crossbar</li></ul>

<b>Options</b>	Options: - EG8380: pair of turntables - PE0003: 6-movement front sliding plate for technical control - PE7000: 3T pneumatic lifting crossbar - PE0008: access ramp extension 1600mm
<b>Advice</b>	Please contact us for installation and start-up. Within the framework of the warranty, installation and start-up must be carried out by a professional. Transportation costs not included.
<b>Warranty period</b>	2 years
<b>Power</b>	2600W
<b>Voltage</b>	400V
<b>Product weight (kg)</b>	2,250 kg
<b>Maximum load (T)</b>	5 T
<b>Tariff code</b>	Tariff Equipment (TE)



CLAS EQUIPEMENTS  
83, chemin de la CROUZA  
73800 CHIGNIN  
France

Tel : +33 (0) 4 79 72 62 22  
Fax :

Monday to Friday - From 8 to 12h  
and from 13h30 to 17h30 (16h30 on  
Friday)