

SMOKE LEAK DETECTOR

Reference : AC 0411BL



Item name SMOKE LEAK DETECTOR

EAN code 3701555311432

Text Thanks to its compact size, this machine is easily transportable, allowing intervention in the entire workshop.
Its integrated compressor eliminates the need for an air supply.
Compatible with the majority of the fleet, connected to the battery terminals, it allows quick diagnosis of the vehicle's closed circuits (turbo, exhaust, cooling, etc.).

To detect micro leaks on the circuits:

- vacuum (excluding EVAP valve, components and diaphragm not resistant to 1bar pressure)
- exhaust
- turbo insulation (excluding pneumatic Wasgate, may entail certain risks 1bar pressure)
- oil pan
- admission
- cooling

This device considerably reduces leak detection time by diffusing an opaque, fine and instantly identifiable smoke on even the smallest leaks.

Without any risk for the user and the vehicle.

Specifications Specifications:
- power supply: 12V
- output pressure: 1.2 bar for turbo system

- flow rate: 8L/min
- smoke control
- mode of operation: air only or smoke
- control manometer
- oil capacity: 50ml
- mineral oil (included)
- supplied with its accessories
- test fluid 250 ml = 35 hours of use
- weight: 3,7Kg
- dimensions: 180x125x210mm

Contents

Contents:

- main unit
- accessory case
- adapter cone
- power cable
- smoke distribution pipe
- funnel
- universal inflatable plug
- pocket replacement rubber
- test fluid (250 ml)
- oil filler cap adapter (for most BMW vehicles)
- smoke diffuser
- EVAP system accessory kit (fuel vapour recovery system)
- set of blanking plugs

Warranty period

2 years

Tension

12V

More

Use oiler

Product weight

4.50 kg

Video link

<https://www.youtube.com/watch?v=PXWDq3sS5Mg>

Capacity (ml)

50.00 ml

Capacity (l)

0.05 l

Tariff code

Tariff Normal (TN)

Product range

B-Line

Warranty Procedure

DIAGNOSTIC



CLAS EQUIPEMENTS
83, chemin de la CROUZA
73800 CHIGNIN
France

Tel : +33 (0) 4 79 72 62 22
Fax :

Monday to Friday - From 8 to
12h30 and from 14h to 17h30
(16h30 on Friday)