

## 4 columns post lift flat oscillation track 400V 5.T

Reference : PE 4101T



<b>Item name</b>	4 columns post lift flat oscillation track 400V 5.T
<b>Bar code</b>	3701555318059
<b>Text</b>	<p>Electro-hydraulic Post lift ideally designed for geometry and technical inspection, with manual tilting plates and optional turntable slots.</p> <p>Suitable for mechanical work, passenger cars, light commercial vehicles and construction equipment.</p> <p>Work comfort: One-piece access ramps, quick and easy vehicle positioning.</p> <p>Fast, easy vehicle positioning with low ground clearance, for rapid repair or inspection, 5160mm long tracks.</p> <p>Equipped with rails for optional lifting crossbar. PE 7100</p> <p>Optional parking kit for 2 cars. PE 4103.</p>
<b>Product highlight</b>	equipped with an air supply under the rails
<b>Specifications</b>	<p>Specifications :</p> <ul style="list-style-type: none"><li>- lifting height: 220-1850mm</li><li>- track width/length: 500/5160mm</li><li>- adjustable distance between runways: 820/920mm</li><li>- air supply 8bar</li><li>- drive power: 3kW</li><li>- drive voltage: (3 phases + Neutral) 400V/50Hz</li><li>- maximum safety: single-cylinder lifting, 4-cable synchronized drive</li><li>- pneumatic release of safety catches</li><li>- safety system in case of cable breakage,</li></ul>

- emergency lowering system in the event of power failure
- intermediate stop at 20 cm from the ground for user safety and anti-crushing audible signal
- air outlet with pneumatic connector in the middle of one of the interior platforms, under the rails
- engine protection cover
- 240V electrical outlet on electrical box
- manual oscillating plates
- Epoxy paint

<b>Options</b>	PE 7100 PE 0104
<b>Advice</b>	Please consult us for installation and commissioning. Under warranty, installation and commissioning must be carried out by a professional. Transport costs not included.
<b>Warranty period</b>	2 years
<b>Power</b>	3000W
<b>Voltage</b>	400V
<b>Width</b>	3,185 mm
<b>Height</b>	2,350 mm
<b>Product weight (kg)</b>	1,290 kg
<b>Max. height</b>	1,850 mm
<b>Min. height</b>	220 mm
<b>Drive through width</b>	2,830 mm
<b>Maximum load (T)</b>	5 T
<b>Tariff code</b>	Tariff Equipment (TE)
<b>Composition of nomenclature</b>	1 x PE 4101T-1 - 4 columns post lift flat oscillation track 400V 5T 1/1 4 x <a href="#">SA 3012 - Hv46 hydraulic oil 5l</a>
<b>Warranty Procedure</b>	INTERVENTION
<b>Customer benefit</b>	Supplied with HV46 hydraulic oil and ground fixing kit
<b>Pneumatic power supply required</b>	YES
<b>Circuit breaker/Cable section</b>	16A D / 5x2.5mm <sup>2</sup>
<b>Soil quality</b>	>20cm Béton C20/25

**2**  
WARRANTY

  
**400V**



TE

**CLAS EQUIPEMENTS**  
83, chemin de la CROUZA  
73800 CHIGNIN  
France

Tel : +33 (0) 4 79 72 62 22  
Fax :

Monday to Friday - From 8 to 12h  
and from 13h30 to 17h30 (16h30 on  
Friday)