

4 COLUMNS POST LIFT FLAT OSCILLATION TRACK 400V 5.T

Reference : PE 4101T



Item name	4 COLUMNS POST LIFT FLAT OSCILLATION TRACK 400V 5.T
Bar code	3701555318059
Text	<p>Electro-hydraulic Post lift ideally designed for geometry and technical inspection, with manual oscillating plates and optional turntable slots.</p> <p>Suitable for mechanical work, passenger cars, light commercial vehicles, motorhomes and construction equipment.</p> <p>Working comfort: One-piece access ramps for fast, easy vehicle positioning.</p> <p>Fast, easy vehicle positioning with low ground clearance, for rapid repair or inspection, 5160mm long tracks.</p> <p>Equipped with rails for optional lifting crossbar. PE 7100</p> <p>Optional parking kit for 2 cars. PE 4103.</p>
Product highlight	equipped with an air supply under the rails
Specifications	<p>Specifications:</p> <ul style="list-style-type: none">- lifting height: 220-1850mm- track width/length: 500/5160mm- adjustable distance between runways: 820/920mm- air supply 8bar- drive power: 3kW- drive voltage: (3 ~) 400V/50 V/Hz- maximum safety: single-cylinder lifting, synchronization driven by 4 cables- pneumatic release of safety catches- safety system in case of cable breakage,

- emergency lowering system in the event of power failure
- intermediate stop at 20 cm from the ground for user safety and anti-crushing audible signal
- air outlet with pneumatic connector in the middle of one of the inner platforms, under the rails
- motor protection cover
- 240V electrical socket on electrical box
- manual oscillating plates
- Epoxy paint

Options	PE 7100 PE 0104
Advice	<p>Installation et mise en service, nous consulter.</p> <p>Dans le cadre de la garantie, l'installation et la mise en service doivent être effectuées par un professionnel.</p> <p>Frais de transport non inclus.</p>
Warranty period	2 years
Power	3000W
Voltage	400V
Width	3,185 mm
Height	2,350 mm
Product weight (kg)	1,290 kg
Max. height	1,850 mm
Min. height	220 mm
Drive through width	2,830 mm
Maximum load (T)	5 T
Tariff code	Tariff Equipment (TE)
Composition of nomenclature	<p>1 x PE 4101T-1 - 4 COLUMNS POST LIFT FLAT OSCILLATION TRACK 400V 5T 1/1 4 x SA 3012 - HV46 HYDRAULIC OIL 5L</p>
Warranty Procedure	INTERVENTION
Customer benefit	Supplied with HV46 hydraulic oil and ground fixing kit
Pneumatic power supply required	YES
Circuit breaker/Cable section	16A D / 5x2.5mm ²
Soil quality	>20cm Béton C20/25



TE

CLAS EQUIPEMENTS
83, chemin de la CROUZA
73800 CHIGNIN
France

Tel : +33 (0) 4 79 72 62 22
Fax :

Monday to Friday - From 8 to 12h
and from 13h30 to 17h30 (16h30 on
Friday)