4 columns post lift flat oscillation track 400V 5.T

Reference : PE 4101T



Item name	4 columns post lift flat oscillation track 400V 5.T
Bar code	3701555318059
Text	Electro-hydraulic post lift ideally designed for wheel alignment and vehicle inspections, featuring manual swing plates and mounting points for optional turntables. Suitable for mechanics work on passenger cars and LCVs. Work comfort: One-piece access ramps for quick and easy vehicle positioning. Quick and easy positioning of vehicles with low ground clearance, enabling rapid repairs or inspections; 5,160 mm-long lift tracks Versatile: Integrated rails allow for the use of an optional lifting crossbeam (PE 7100). Optional: A parking kit for storing 2 cars. PE 4103.
Product highlight	equipped with an air supply under the rails
Specifications	Specifications: - Lifting height: 220–1,850 mm - Track width/length: 500/5,160 mm - Adjustable track spacing: 820/920 mm - Air supply: 8 bar - Drive power: 3 kW - Drive voltage: (3-phase + neutral) 400 V/50 Hz - Maximum safety: single-cylinder lift, synchronization via 4 cables - Pneumatic release of safety locks - Safety system in case of cable breakage - Emergency descent system in case of power failure

	- Intermediate stop 20 cm above the ground for user safety and an anti-crushing audible alarm - Air outlet with pneumatic connector in the center of one of the interior platforms, beneath the rails - Engine protective cover - 240V electrical outlet on the electrical box - Manual swing plates - Epoxy paint
Options	PE 7100 PE 0104
Advice	Please consult us for installation and commissioning. Under warranty, installation and commissioning must be carried out by a professional. Transport costs not included.
Warranty period	2 years
Power	3000W
Voltage	400V
Width	3,185 mm
Height	2,350 mm
Product weight (kg)	1,290 kg
Max. height	1,850 mm
Min. height	220 mm
Drive through width	2,830 mm
Maximum load (T)	5 T
Tariff code	Tariff Equipment (TE)
Composition of nomenclature	1 x PE 4101T-1 - 4 columns post lift flat oscillation track 400V 5T 1/1 4 x SA 3012 - Hv46 hydraulic oil 5l
Warranty Procedure	INTERVENTION
Customer benefit	Supplied with HV46 hydraulic oil and ground fixing kit
Pneumatic power supply required	YES
Circuit breaker/Cable section	16A D tetra / 5x2.5mm² (3PH + N + T)
Soil quality	>20cm Béton C20/25



CLAS EQUIPEMENTS
83, chemin de la CROUZA
73800 CHIGNIN
France

Tel : +33 (0) 4 79 72 62 22
Fax :

Monday to Friday - From 8 to 12h and from 13h30 to 17h30 (16h30 on Friday)