

## 4 columns post lift 5T auxiliary lift 4T

Reference : PE 4102T



<b>Item name</b>	4 columns post lift 5T auxiliary lift 4T
<b>Bar code</b>	3701555318097
<b>Text</b>	<p>Suitable for mechanical work, light commercial vehicles, construction equipment, ideally designed for geometry with pneumatic oscillating plates and optional turntable slots. Auxiliary 4T lifts with galvanized double extensions. Working comfort: access platforms equipped with auxiliary lifts. Fast, easy vehicle positioning with low ground clearance, for rapid repair or inspection, 5160mm long tracks. Equipped with rails for optional lifting crossbar. PE 7100 Optional parking kit for 2 cars: PE 4103.</p>
<b>Product highlight</b>	4T auxiliary lifts with galvanized double extensions
<b>Specifications</b>	<p>Specifications :</p> <ul style="list-style-type: none"><li>- lifting height: 220-1850mm</li><li>- track width/length: 610/5160mm</li><li>- adjustable distance between runways: 910-1010mm</li><li>- required air supply 6-8 bar.</li><li>- drive power: 3kW</li><li>- drive voltage: (3 phases + Neutral) 400V/50Hz</li><li>- maximum safety: single-cylinder lifting, synchronization driven by 4 cables</li><li>- pneumatic release of safety catches</li><li>- auxiliary lifts 5T capacity</li><li>- safety system in case of cable breakage,</li></ul>

- emergency lowering system in case of power failure
- intermediate stop at 20 cm from the ground for operator safety, and anti-crushing audible signal
- motor protection cover
- 240V power socket on electrical box
- pneumatic oscillating plates
- Epoxy paint

**Advice** Please consult us for installation and commissioning.  
Under warranty, installation and commissioning must be carried out by a professional.  
Transport costs not included.

<b>Warranty period</b>	2 years
<b>Power</b>	3000W
<b>Voltage</b>	400V
<b>Width</b>	3,185 mm
<b>Height</b>	2,350 mm
<b>Product weight (kg)</b>	1,990 kg
<b>Max. height</b>	1,850 mm
<b>Min. height</b>	220 mm
<b>Drive through width</b>	2,830 mm
<b>Maximum load (T)</b>	5 T
<b>Tariff code</b>	Tariff Equipment (TE)
<b>Composition of nomenclature</b>	1 x PE 4102T-1 - 4 columns post lift 5T auxiliary lift 1/1 4 x <a href="#">SA 3012 - Hv46 hydraulic oil 5l</a>

#### **Warranty Procedure** INTERVENTION

<b>Customer benefit</b>	Supplied with HV46 hydraulic oil and ground fixing kit
<b>Pneumatic power supply required</b>	YES
<b>Circuit breaker/Cable section</b>	16A D / 5x2.5mm <sup>2</sup>
<b>Soil quality</b>	>20cm Béton C20/25



CLAS EQUIPEMENTS  
83, chemin de la CROUZA  
73800 CHIGNIN  
France

Tel : +33 (0) 4 79 72 62 22  
Fax :

Monday to Friday - From 8 to 12h  
and from 13h30 to 17h30 (16h30 on  
Friday)