

4 COLUMNS POST LIFT 5T AUXILIARY LIFT 4T

Reference : PE 4102T



Item name	4 COLUMNS POST LIFT 5T AUXILIARY LIFT 4T
Bar code	3701555318097
Text	<p>Suitable for mechanical work, passenger cars, LCVs, motorhomes, construction equipment, ideally designed for geometry with pneumatic oscillating plates and optional turntable slots.</p> <p>Auxiliary 4T lifts with galvanized double extensions.</p> <p>Working comfort: access platforms equipped with auxiliary lifts.</p> <p>Fast, easy vehicle positioning with low ground clearance, for rapid repair or inspection, 5160mm long tracks.</p> <p>Equipped with rails for optional lifting crossbar. PE 7100</p> <p>Optional parking kit for 2 cars: PE 4103.</p>
Product highlight	4T auxiliary lifts with double galvanized extensions
Specifications	<p>Specifications:</p> <ul style="list-style-type: none">- lifting height: 220-1850mm- track width/length: 610/5160mm- adjustable distance between runways: 910-1010mm- required air supply 6-8 bar.- drive power: 3kW- drive voltage: (3 phases + Neutral) 400V/50Hz- maximum safety: single-cylinder lifting, synchronization driven by 4 cables- pneumatic release of safety catches- auxiliary lifts 5T capacity

- safety system in case of cable breakage,
- emergency lowering system in case of power failure
- intermediate stop at 20 cm from the ground for operator safety, and anti-crushing audible signal
- motor protection cover
- 240V power socket on electrical box
- pneumatic oscillating plates
- epoxy paint

Advice

Installation et mise en service, nous consulter.

Dans le cadre de la garantie, l'installation et la mise en service doivent être effectuées par un professionnel.

Frais de transport non inclus.

Warranty period 2 years

Power 3000W

Voltage 400V

Width 3,185 mm

Height 2,350 mm

Product weight (kg) 1,990 kg

Max. height 1,850 mm

Min. height 220 mm

Drive through width 2,830 mm

Maximum load (T) 5 T

Tariff code Tariff Equipment (TE)

Composition of nomenclature 1 x PE 4102T-1 - 4 COLUMNS POST LIFT 5T AUXILIARY LIFT 1/1
4 x [SA 3012 - HV46 HYDRAULIC OIL 5L](#)

Warranty Procedure

INTERVENTION

Customer benefit Supplied with HV46 hydraulic oil and ground fixing kit

Pneumatic power supply required YES

Circuit breaker/Cable section 16A D / 5x2.5mm²

Soil quality >20cm Béton C20/25



CLAS EQUIPEMENTS
83, chemin de la CROUZA
73800 CHIGNIN
France

Tel : +33 (0) 4 79 72 62 22
Fax :

Monday to Friday - From 8 to 12h
and from 13h30 to 17h30 (16h30 on
Friday)