4 columns post lift 5T auxiliary lift 4T

Reference : PE 4102T



Item name	4 columns post lift 5T auxiliary lift 4T
Bar code	3701555318097
Text	Suitable for mechanics work on passenger cars and LCVs; ideally designed for wheel alignment with these pneumatic swing plates and mounting points for optional turntables. 4-ton auxiliary lifts with double galvanized extensions. Work comfort: access ramps equipped with auxiliary lifting devices. Quick and easy positioning of vehicles with low ground clearance, enabling rapid repairs or inspections; ramps are 5160mm long. Versatile: Integrated rails allow for the use of an optional lifting crossbeam (PE 7100). Optional: A parking kit for storing 2 cars: PE 4103.
Product highlight	4T auxiliary lifts with galvanized double extensions
Specifications	Specifications: - Lifting height: 220–1,850 mm - Width/length of track: 610/5,160 mm - Adjustable distance between bearings: 910–1,010 mm - Required air pressure: 6–8 bar - Drive power: 3 kW - Drive voltage: (3-phase + neutral) 400 V/50 Hz - Maximum safety: single-cylinder lift, 4-cable synchronized drive - Pneumatic release of safety locks - Auxiliary lifting capacity: 5 metric tons - Safety system in case of cable breakage

	- Emergency lowering system in case of power failure - Intermediate stop 20 cm above the ground for user safety and an anti-crushing audible alarm - Motor protective cover - 240V electrical outlet on the electrical enclosure - Pneumatic swing plates - Epoxy paint
Advice	Please consult us for installation and commissioning. Under warranty, installation and commissioning must be carried out by a professional. Transport costs not included.
Warranty period	2 years
Power	3000W
Voltage	400V
Width	3,185 mm
Height	2,350 mm
Product weight (kg)	1,990 kg
Max. height	1,850 mm
Min. height	220 mm
Drive through width	2,830 mm
Maximum load (T)	5 T
Tariff code	Tariff Equipment (TE)
Composition of nomenclature	1 x PE 4102T-1 - 4 columns post lift 5T auxiliary lift 1/1 4 x SA 3012 - Hv46 hydraulic oil 5l
Warranty Procedure	INTERVENTION
Customer benefit	Supplied with HV46 hydraulic oil and ground fixing kit
Pneumatic power supply required	YES
Circuit breaker/Cable section	16A D tetra / 5x2.5mm² (3PH + N + T)
Soil quality	>20cm Béton C20/25



CLAS EQUIPEMENTS
83, chemin de la CROUZA
73800 CHIGNIN
France

Tel : +33 (0) 4 79 72 62 22
Fax :

Monday to Friday - From 8 to 12h and from 13h30 to 17h30 (16h30 on Friday)