

## 4 COLUMNS POST LIFT 5T AUXILIARY LIFT 4T

Reference : PE 4102T



<b>Item name</b>	4 COLUMNS POST LIFT 5T AUXILIARY LIFT 4T
<b>Bar code</b>	3701555318097
<b>Text</b>	<p>Suitable for mechanical work, passenger cars, LCVs, motorhomes, construction equipment, ideally designed for geometry with pneumatic oscillating plates and optional turntable slots.</p> <p>Auxiliary 4T lifts with galvanized double extensions.</p> <p>Working comfort: access platforms equipped with auxiliary lifts.</p> <p>Fast, easy vehicle positioning with low ground clearance, for rapid repair or inspection, 5160mm long tracks.</p> <p>Equipped with rails for optional lifting crossbar. PE 7100</p> <p>Optional parking kit for 2 cars: PE 4103.</p>
<b>Product highlight</b>	4T auxiliary lifts with double galvanized extensions
<b>Specifications</b>	<p>Specifications:</p> <ul style="list-style-type: none"> <li>- lifting height: 220-1850mm</li> <li>- track width/length: 610/5160mm</li> <li>- adjustable distance between runways: 910-1010mm</li> <li>- required air supply 6-8 bar.</li> <li>- drive power: 3kW</li> <li>- drive voltage: (3 phases + Neutral) 400V/50Hz</li> <li>- maximum safety: single-cylinder lifting, synchronization driven by 4 cables</li> <li>- pneumatic release of safety catches</li> <li>- auxiliary lifts 5T capacity</li> </ul>

- safety system in case of cable breakage,
- emergency lowering system in case of power failure
- intermediate stop at 20 cm from the ground for operator safety, and anti-crushing audible signal
- motor protection cover
- 240V power socket on electrical box
- pneumatic oscillating plates
- epoxy paint

**Advice** Installation et mise en service, nous consulter.  
 Dans le cadre de la garantie, l'installation et la mise en service doivent être effectuées par un professionnel.  
 Frais de transport non inclus.

<b>Warranty period</b>	2 years
<b>Power</b>	3000W
<b>Voltage</b>	400V
<b>Width</b>	3,185 mm
<b>Height</b>	2,350 mm
<b>Product weight (kg)</b>	1,990 kg
<b>Max. height</b>	1,850 mm
<b>Min. height</b>	220 mm
<b>Drive through width</b>	2,830 mm
<b>Maximum load (T)</b>	5 T
<b>Tariff code</b>	Tariff Equipment (TE)
<b>Composition of nomenclature</b>	1 x PE 4102T-1 - 4 COLUMNS POST LIFT 5T AUXILIARY LIFT 1/1 4 x <a href="#">SA 3012 - HV46 HYDRAULIC OIL 5L</a>

#### **Warranty Procedure** INTERVENTION

<b>Customer benefit</b>	Supplied with HV46 hydraulic oil and ground fixing kit
<b>Pneumatic power supply required</b>	YES
<b>Circuit breaker/Cable section</b>	16A D / 5x2.5mm <sup>2</sup>
<b>Soil quality</b>	>20cm Béton C20/25



**\*Public price Exl. Tax : €13,699**

\*Applicable user fees from 01/09/2025 to 31/08/2026

CLAS EQUIPEMENTS  
83, chemin de la CROUZA  
73800 CHIGNIN  
France

Tel : +33 (0) 4 79 72 62 22  
Fax :

Monday to Friday - From 8 to 12h  
and from 13h30 to 17h30 (16h30 on  
Friday)