

Mobile scissor lift dual cylinder low raise 240V 3T

Reference : PE 6102M



Item name	Mobile scissor lift dual cylinder low raise 240V 3T
Bar code	3701555318066
Text	Particularly well-suited to paint, bodywork and quick service operations. Easy access: low ground clearance of 115mm, lockable access ramps to extend platforms. Working comfort: easy to move thanks to removable wheels and drawbar. Easy storage of components on the console.
Product highlight	Supplied with mobility kit 100% electric
Specifications	Specifications : <ul style="list-style-type: none">- lifting height: 115-1000mm- track width/length: 460/1410-2010mm- control panel- drive power: 3kW- drive voltage: 240V/50Hz- emergency lowering system in case of power failure- intermediate stop 20 cm above ground for operator safety and anti-crushing audible signal- motor protection cover- rack and pinion safety device- electric lock release (no need for pneumatic power supply)
Advice	Installation et mise en service, nous consulter. Dans le cadre de la garantie, l'installation et la mise en service doivent être effectuées par

un professionnel.
Frais de transport non inclus.

Warranty period	2 years
Power	3000W
Voltage	240V
Length (mm)	2,010 mm
Width	1,950 mm
Height	1,000 mm
Product weight (kg)	548 kg
Max. height	1,000 mm
Min. height	115 mm
Maximum load (T)	3 T
Tariff code	Tariff Equipment (TE)
Composition of nomenclature	1 x PE 6102M-1 - Mobile scissor lift dual cylinder low raise 240V 3T 1/3 1 x PE 6102M-2 - Mobile scissor lift dual cylinder low raise 240V 3T 2/3 1 x PE 6102M-3 - Mobile scissor lift dual cylinder low raise 240V 3T 3/3 2 x SA 3012 - Hv46 hydraulic oil 5l

Warranty Procedure INTERVENTION

Pneumatic power supply required	NO
Circuit breaker/Cable section	16A D / 3x2.5mm ²
Soil quality	>20cm Béton C20/25



CLAS EQUIPEMENTS
83, chemin de la CROUZA
73800 CHIGNIN
France

Tel : +33 (0) 4 79 72 62 22
Fax :

Monday to Friday - From 8 to 12h
and from 13h30 to 17h30 (16h30 on
Friday)