2 post lifts asymmetrical 400V base 4T 4 arms 1.10 + 1.50m

Reference : PE 2100T



Item name	2 post lifts asymmetrical 400V base 4T 4 arms 1.10 + 1.50m
Bar code	3701555318004
Text	Lift designed to facilitate the installation and alignment of columns thanks to its 40-mm-thick base. When used with the PE 2101 option, it addresses the issue of screeds that do not meet the minimum thickness requirement of 200 mm (allows for coverage down to 150 mm) or that have slight flatness issues. Electro-hydraulic post lift. Cable-driven push cylinder; carriage driven by chain. Asymmetrical telescoping arms with three-stage arms measuring 1,100 mm and 1,500 mm.
Product highlight	Low-thickness passage
Specifications	Specifications: - Lifting height: 100–2,100 mm - Drive power: 2.2 kW - Drive voltage: (3-phase + neutral) 400 V/50 Hz - Adjustable stops on lead screw, travel: 70–140 mm - Automatic release of safety locks - Emergency lowering system in case of power failure - System synchronization: via cable - Intermediate stop 20 cm above the floor for user safety and an anti-pinch audible alarm - Motor protective cover

	- Door protection on the columns - 240V electrical outlet on the control box - Protective strip for the cylinder, chain, and cables included on each column - Comes with 4 x 70mm risers and their mounts - Epoxy paint finish
Advice	Installation et mise en service, nous consulter. Dans le cadre de la garantie, l'installation et la mise en service doivent être effectuées par un professionnel. Frais de transport non inclus.
Warranty period	2 years
Power	2200W
Voltage	400V
Length (mm)	3,440 mm
Width	44 mm
Height	2,965 mm
Product weight (kg)	781 kg
Max. height	2,100 mm
Min. height	100 mm
Drive through width	2,460 mm
Maximum load (T)	4 T
Tariff code	Tariff Equipment (TE)
Composition of nomenclature	1 x PE 2102 - 2 columns with basement 400V 4T without arms 1 x PE 2103T - Engine bloc 2 columns post lift 4T 1 x PE 2104 - 2 columns post lift with basement accessories 4T 1 x PE 2111 - Pair of arms with block 1.50m and foot protection 2 x SA 3012 - Hv46 hydraulic oil 5l 1 x PE 2117 - 2 columns post lift base 4T low passage 1 x PE 2110 - Pair of arms with block 1.10m and foot protection
Warranty Procedure	INTERVENTION
Customer benefit	Supplied with HV46 hydraulic oil and ground fixing kit
Pneumatic power supply required	NO
Circuit breaker/Cable section	10A D tetra / 5x2.5mm² (3PH + N + T)
Soil quality	>20cm Béton C20/25



***Public price Exl. Tax : €3,999**

*Applicable user fees from 01/09/2026 to 31/08/2027

CLAS EQUIPEMENTS
83, chemin de la CROUZA
73800 CHIGNIN
France

Tel : +33 (0) 4 79 72 62 22
Fax :

Monday to Friday - From 8 to 12h and from 13h30 to 17h30 (16h30 on Friday)