2 column high passage deck 5.10m 400V 6T 4 arm articules

Reference : PE 2350T



Item name	2 column high passage deck 5.10m 400V 6T 4 arm articules
Bar code	3701555318042
Text	Particularly suited to repair work on extended utility vehicles, 4x4s, microcars, hybrids and electrics. Electro-hydraulic post lift. Direct push cylinder on carriage. Arms with adjustable joints. Hose and cable routing from the top for optimum working comfort, allowing free access to equipment under the vehicle (cylinders, oil recuperator, battery removal, etc.), facilitating workshop cleaning. Hydraulic power pack: equipped with a position safety device for precise intervention, gearbox assembly, nut alignment, etc. Multiple lifting capacities thanks to 4 multi-adjustable articulated arms. Cylinder and cable protection strip included on each column.
Product highlight	6T capacity Multi-position arm
Specifications	Specifications: - Lifting height: 95–1,850 mm - Drive power: 2.2 kW - Drive voltage: (3-phase + neutral) 400 V/50 Hz - Concrete strength/grade: 200 mm–C20/25 - Adjustable screw-type stops with 70–140 mm travel

	- Electric release of safety locks - Emergency lowering system in case of power failure - System synchronization: via cable - Intermediate stop 20 cm above the floor for user safety and an anti-crushing audible alarm - Motor protective cover - Door protection on the columns - 240V electrical outlet on the control box - Protective strip for the cylinder and cables included on each column - Comes with 4 x 70mm risers and their brackets - Epoxy paint finish
Advice	Installation et mise en service, nous consulter. Mise à disposition d'une nacelle impérative. Dans le cadre de la garantie, l'installation et la mise en service doivent être effectuées par un professionnel. Frais de transport non inclus.
Warranty period	2 years
Power	2200W
Voltage	400V
Length (mm)	4,000 mm
Height	5,000 mm
Product weight (kg)	1,114 kg
Max. height	1,850 mm
Min. height	95 mm
Drive through width	3,190 mm
Maximum load (T)	6 T
Tariff code	Tariff Equipment (TE)
Composition of nomenclature	1 x PE 2340 - 2 columns high passage 400V 6T without arms 1 x PE 2355T - Engine bloc 2 columns post lift 6T 2 x PE 2341 - Pair of articulated arms for 6T 1 x PE 2343 - High passage extension 5m00 for 6T 2 x SA 3012 - Hv46 hydraulic oil 5l
Warranty Procedure	INTERVENTION
Customer benefit	Supplied with HV46 hydraulic oil and ground fixing kit
Pneumatic power supply required	NO
Circuit breaker/Cable section	10A D tetra / 5x2.5mm² (3PH + N + T)

Soil quality >20cm Béton C20/25



CLAS EQUIPEMENTS
83, chemin de la CROUZA
73800 CHIGNIN
France

Tel : +33 (0) 4 79 72 62 22
Fax :

Monday to Friday - From 8 to 12h and from 13h30 to 17h30 (16h30 on Friday)