
Extra-flat 2-cylinder 400V 3.6T double-scissor lift for free-standing or built-in installation

Reference : PE 6236T



Item name	Extra-flat 2-cylinder 400V 3.6T double-scissor lift for free-standing or built-in installation
Bar code	3701555318073
Text	Particularly well-suited for painting, body repair, and quick-service operations. Installation options: free-standing or built-in. Versatile and space-saving, this scissor lift makes it easy to service low-profile vehicles thanks to its access height of just 110 mm. Its lockable access ramps allow the platforms to be extended to accommodate the vehicle’s wheelbase. The master-slave hydraulic system, combined with a rack-and-pinion mechanism, ensures synchronized lifting and double safety.
Product highlight	Can be used free-standing or built-in
Specifications	Specifications: - Lifting height: 110–1,880 mm - Width/length of bearing rails: 630/1,480–2,090 mm - Photocell synchronization system - Required air supply: 6–8 bar - Control panel - Drive power: 3 kW - Drive voltage: (3-phase + neutral) 400 V/50 Hz - Emergency descent system in case of power failure - Intermediate stop 20 cm above the floor for user safety and an anti-crushing audible alarm

	- Comes with 4 bumpers
Advice	Installation et mise en service, nous consulter. Dans le cadre de la garantie, l'installation et la mise en service doivent être effectuées par un professionnel. Frais de transport non inclus.
Warranty period	2 years
Power	3000W
Voltage	400V
Length (mm)	2,090 mm
Width	2,110 mm
Height	960 mm
Product weight (kg)	904 kg
Max. height	1,880 mm
Min. height	110 mm
Maximum load (T)	3.60 T
Tariff code	Tariff Equipment (TE)
Composition of nomenclature	1 x PE 6236T-1 - Double scissor lift 2cylinder 400V 3.6T low profile on/in-ground 1/3 1 x PE 6236T-2 - Double scissor lift 2cylinder 400V 3.6T low profile on/in-ground 2/3 1 x PE 6236T-3 - Double scissor lift 2cylinder 400V 3.6T low profile on/in-ground 3/3 3 x SA 3012 - Hv46 hydraulic oil 5l
Warranty Procedure	INTERVENTION
Customer benefit	Supplied with HV46 hydraulic oil and ground fixing kit
Pneumatic power supply required	YES
Circuit breaker/Cable section	16A D tetra / 5x2.5mm² (3PH + N + T)
Soil quality	>20cm Béton C20/25
Quick tip videos	Cliquez sur l'opération qui vous intéresse pour voir la **vidéo**:





PURGE ET SYNCHRONISATION DES VERINS

CLAS EQUIPEMENTS
83, chemin de la CROUZA
73800 CHIGNIN
France

Tel : +33 (0) 4 79 72 62 22
Fax :

Monday to Friday - From 8 to 12h and from 13h30 to 17h30 (16h30 on Friday)