

Extra-low 2-cylinder, 400V, 3.6T double scissor lift for free-standing or built-in installation

Reference : PE 6236T



Item name	Extra-low 2-cylinder, 400V, 3.6T double scissor lift for free-standing or built-in installation
Bar code	3701555318073
Text	Particularly suited to paint, body repair and quick service activities. Choice of installation: free-standing or built-in. Easy access: low ground clearance of 110mm, lockable ramps to extend platforms. Maximum comfort and safety: double hydraulic master-slave safety system, combined with a rack and pinion system, to maintain the lift in position for long periods.
Product highlight	Can be used free-standing or built-in
Specifications	Specifications: <ul style="list-style-type: none">- Lifting height: 110–1,880 mm- Bearing width/length: 630/1,480–2,090 mm- Synchronization system: photocell- Required air pressure: 6–8 bar.- control panel- drive power: 3 kW- drive voltage: (3-phase + neutral) 400 V/50 Hz- Emergency descent system in case of power failure- Intermediate stop 20 cm above the floor for user safety and an anti-pinch audible alarm- Comes with 4 bumpers


Advice	Installation et mise en service, nous consulter. Dans le cadre de la garantie, l'installation et la mise en service doivent être effectuées par un professionnel. Frais de transport non inclus.
Warranty period	2 years
Power	3000W
Voltage	400V
Length (mm)	2,090 mm
Width	2,110 mm
Height	960 mm
Product weight (kg)	904 kg
Max. height	1,880 mm
Min. height	110 mm
Maximum load (T)	3.60 T
Tariff code	Tariff Equipment (TE)
Composition of nomenclature	1 x PE 6236T-1 - Double scissor lift 2cylinder 400V 3.6T low profile on/in-ground 1/3 1 x PE 6236T-2 - Double scissor lift 2cylinder 400V 3.6T low profile on/in-ground 2/3 1 x PE 6236T-3 - Double scissor lift 2cylinder 400V 3.6T low profile on/in-ground 3/3 3 x SA 3012 - Hv46 hydraulic oil 5l

Warranty Procedure INTERVENTION

Customer benefit	Supplied with HV46 hydraulic oil and ground fixing kit
Pneumatic power supply required	YES
Circuit breaker/Cable section	16A D tetra / 5x2.5mm ² (3PH + N + T)
Soil quality	>20cm Béton C20/25

Quick tip videos

Cliquez sur l'opération qui vous intéresse pour voir la **vidéo**:



[PURGE ET SYNCHRONISATION DES VERINS](#)

CLAS EQUIPEMENTS
83, chemin de la CROUZA
73800 CHIGNIN
France

Tel : +33 (0) 4 79 72 62 22
Fax :

Monday to Friday - From 8 to 12h
and from 13h30 to 17h30 (16h30 on
Friday)