Double scissor lift dual cylinder 400V 4T in-ground

Reference : PE 6340T



Item name	Double scissor lift dual cylinder 400V 4T in-ground
Bar code	3701555318110
Text	Particularly well-suited for SUVs, 4x4s, and LCVs thanks to its 4-metric-ton capacity. Built-in. The master-slave hydraulic system, combined with a rack-and-pinion mechanism, ensures synchronized lifting and double safety. Galvanized platforms with two extensions.
Product highlight	Ideal for SUVs and 4x4s
Specifications	Specifications: - Lifting height: 0–2,120 mm - Width/length of bearing rails: 565/1,660–2,060 mm - Photocell synchronization system - Required air supply: 6–8 bar - Control panel - Drive power: 3 kW - Drive voltage: (3-phase + neutral) 400 V/50 Hz - Emergency descent system in case of power failure - Intermediate stop 20 cm above the floor for user safety and an anti-crushing audible alarm
Advice	Installation et mise en service, nous consulter. Dans le cadre de la garantie, l'installation et la mise en service doivent être effectuées par un professionnel.

	Frais de transport non inclus.
Warranty period	2 years
Power	3000W
Voltage	400V
Product weight (kg)	755 kg
Max. height	2,120 mm
Maximum load (T)	4 T
Tariff code	Tariff Equipment (TE)
Composition of nomenclature	1 x PE 6340T-1 - Double scissor lift dual cylinder 400V 4T in-ground 1/4 1 x PE 6340T-2 - Double scissor lift dual cylinder 400V 4T in-ground 2/4 1 x PE 6340T-3 - Double scissor lift dual cylinder 400V 4T in-ground 3/4 1 x PE 6340T-4 - Double scissor lift dual cylinder 400V 4T in-ground 4/4 3 x SA 3012 - Hv46 hydraulic oil 5l
Warranty Procedure	INTERVENTION
Customer benefit	Supplied with HV46 hydraulic oil and ground fixing kit
Pneumatic power supply required	YES
Circuit breaker/Cable section	16A D tetra / 5x2.5mm² (3PH + N + T)
on-ground/in-ground	in-ground
Soil quality	>20cm Béton C20/25



CLAS EQUIPEMENTS
83, chemin de la CROUZA
73800 CHIGNIN
France

Tel : +33 (0) 4 79 72 62 22
Fax :

Monday to Friday - From 8 to 12h and from 13h30 to 17h30 (16h30 on Friday)