

EXTRA LOW PROFILE SCISSOR LIFT 5.5T AUXILIARY LIFT 4.5T IN-GROUND

Reference : PE 6351T



Item name	EXTRA LOW PROFILE SCISSOR LIFT 5.5T AUXILIARY LIFT 4.5T IN-GROUND
Bar code	3701555318127
Text	<p>Particularly suitable for technical inspection, geometry and repair. Flush-mounted for light and heavy-duty vehicles. Maximum safety: mechanical safety rack on main and auxiliary scissors for position stabilization. Auxiliary lift capacity 4.5T with 2 galvanized extensions. The secondary auxiliary cylinder is chrome-plated for enhanced durability. Oscillating plates with pneumatic locking. Equipped with rails for optional lifting crossbar. PE 7100</p>
Product highlight	ideal undercarriage control
Specifications	<p>Specifications:</p> <ul style="list-style-type: none">- lift height: 0-1980mm- track width/length: 690/5200mm- system synchronization: photo cell- control panel- drive power: 3kw- drive voltage: (3 ~) 400V/50 V/Hz- air supply required 6-8 bar.- oscillating plate pneumatic locking- epoxy paint

- emergency lowering system in case of power failure
- intermediate stop 20 cm above ground for operator safety and anti-crushing audible signal

Advice

Installation et mise en service, nous consulter.

Dans le cadre de la garantie, l'installation et la mise en service doivent être effectuées par un professionnel.

Frais de transport non inclus.

Warranty period

2 years

Power

3000W

Voltage

400V

Length (mm)

5,200 mm

Product weight (kg)

2,536 kg

Max. height

1,980 mm

Maximum load (T)

5.50 T

Tariff code

Tariff Equipment (TE)

Composition of nomenclature

1 x PE 6351T-1 - EXTRA LOW PROFILE SCISSOR LIFT 5.5T AUX. LIFT 4.5T IN-GROUND 1/4

1 x PE 6351T-2 - EXTRA LOW PROFILE SCISSOR LIFT 5.5T AUX. LIFT 4.5T IN-GROUND 2/4

1 x PE 6351T-3 - EXTRA LOW PROFILE SCISSOR LIFT 5.5T AUX. LIFT 4.5T IN-GROUND 3/4

1 x PE 6351T-4 - EXTRA LOW PROFILE SCISSOR LIFT 5.5T AUX. LIFT 4.5T IN-GROUND 4/4

4 x [SA 3012 - HV46 HYDRAULIC OIL 5L](#)

Warranty Procedure

INTERVENTION

Customer benefit

Supplied with HV46 hydraulic oil and ground fixing kit

Pneumatic power supply required

YES

Circuit breaker/Cable section

16A D / 5x2.5mm²

on-ground/in-ground

in-ground

Soil quality

>20cm Béton C20/25



CLAS EQUIPEMENTS
83, chemin de la CROUZA
73800 CHIGNIN
France

Tel : +33 (0) 4 79 72 62 22
Fax :

Monday to Friday - From 8 to 12h
and from 13h30 to 17h30 (16h30 on
Friday)