Extra-low-profile 5.5-metric-ton, 400-volt built-in scissor lift with 4.5-metric-ton auxiliary lifting device

Reference : PE 6351T



Item name	Extra-low-profile 5.5-metric-ton, 400-volt built-in scissor lift with 4.5-metric-ton auxiliary lifting device
Bar code	3701555318127
Text	5.5-metric-ton scissor lift, particularly suited for technical inspections, wheel alignment, and repairs on passenger cars and LCVs Recessed installation for optimal integration into the workshop Maximum safety: mechanical rack-and-pinion locking on the main and auxiliary scissor arms, ensuring perfect stabilization in the working position 4.5T auxiliary lifting, equipped with 2 galvanized extensions to facilitate under-chassis lifting Enhanced durability: auxiliary lifting system cylinder with chrome plating for improved long-term durability Ideal for wheel alignment thanks to the oscillating plates with pneumatic locking Ready to use: comes with 2 swivel platforms. Versatile: integrated rails allow for the use of an optional lifting crossbar (PE 7100).
Product highlight	ideal geometry
Specifications	Specifications: - Lifting height: 0–1,980 mm - Width/length of bearing rails: 690/5,200 mm - Photocell synchronization system - Control panel

	- Drive power: 3 kW - Drive voltage: (3-phase + neutral) 400 V/50 Hz - Required air supply: 6–8 bar - Pneumatically locked swing plates - Epoxy paint finish - Emergency descent system in case of power failure - Intermediate stop 20 cm above the floor for user safety and an anti-crushing audible alarm
Advice	Installation et mise en service, nous consulter. Dans le cadre de la garantie, l'installation et la mise en service doivent être effectuées par un professionnel. Frais de transport non inclus.
Warranty period	2 years
Power	3000W
Voltage	400V
Length (mm)	5,200 mm
Product weight (kg)	2,536 kg
Max. height	1,980 mm
Maximum load (T)	5.50 T
Tariff code	Tariff Equipment (TE)
Composition of nomenclature	1 x PE 6351T-1 - Extra low profile scissor lift 5.5T aux. lift 4.5T in-ground 1/4 1 x PE 6351T-2 - Extra low profile scissor lift 5.5T aux. lift 45T in-ground 2/4 1 x PE 6351T-3 - Extra low profile scissor lift 5.5T aux. lift 4.5T in-ground 3/4 1 x PE 6351T-4 - Extra low profile scissor lift 5.5T aux. lift 4.5T in-ground 4/4 4 x SA 3012 - Hv46 hydraulic oil 5l
Warranty Procedure	INTERVENTION
Customer benefit	Supplied with HV46 hydraulic oil and ground fixing kit
Pneumatic power supply required	YES
Circuit breaker/Cable section	16A D tetra / 5x2.5mm² (3PH + N + T)
on-ground/in-ground	in-ground
Soil quality	>20cm Béton C20/25
Quick tip videos	Cliquez sur l'opération qui vous intéresse pour voir la **vidéo**:



PURGE ET SYNCHRONISATION DES VERINS



CLAS EQUIPEMENTS
83, chemin de la CROUZA
73800 CHIGNIN
France

Tel : +33 (0) 4 79 72 62 22
Fax :

Monday to Friday - From 8 to 12h and from 13h30 to 17h30 (16h30 on Friday)