

Extra low profile scissor lift 5.5T auxiliary lift 4.5T in-ground

Reference : PE 6351T



Item name	Extra low profile scissor lift 5.5T auxiliary lift 4.5T in-ground
Bar code	3701555318127
Text	<p>Particularly suitable for technical inspections, geometries and repairs. Built-in for passenger cars and light commercial vehicles. Maximum safety: mechanical safety rack on main and auxiliary scissors to stabilize position. Auxiliary lift capacity 4.5T with 2 galvanized extensions. The secondary auxiliary cylinder is chrome-plated for enhanced durability. Oscillating plates with pneumatic locking. Equipped with rails for optional lifting crossbar. PE 7100</p>
Product highlight	ideal undercarriage control
Specifications	<p>Specifications :</p> <ul style="list-style-type: none">- lift height: 0-1980mm- track width/length: 690/5200mm- system synchronization: photo cell- control panel- drive power: 3kw- drive voltage: (3 phases + Neutral) 400V/50Hz- air supply required 6-8 bar.- oscillating plates pneumatic locking- epoxy paint- emergency lowering system in case of power failure

- intermediate stop at 20 cm from the ground for user safety and anti-crushing audible signal

Advice Installation et mise en service, nous consulter.
Dans le cadre de la garantie, l'installation et la mise en service doivent être effectuées par un professionnel.
Frais de transport non inclus.

Warranty period 2 years

Power 3000W

Voltage 400V

Length (mm) 5,200 mm

Product weight (kg) 2,536 kg

Max. height 1,980 mm

Maximum load (T) 5.50 T

Tariff code Tariff Equipment (TE)

Composition of nomenclature 1 x PE 6351T-1 - Extra low profile scissor lift 5.5T aux. lift 4.5T in-ground 1/4
1 x PE 6351T-2 - Extra low profile scissor lift 5.5T aux. lift 4.5T in-ground 2/4
1 x PE 6351T-3 - Extra low profile scissor lift 5.5T aux. lift 4.5T in-ground 3/4
1 x PE 6351T-4 - Extra low profile scissor lift 5.5T aux. lift 4.5T in-ground 4/4
4 x [SA 3012 - Hv46 hydraulic oil 5l](#)

Warranty Procedure INTERVENTION

Customer benefit Supplied with HV46 hydraulic oil and ground fixing kit

Pneumatic power supply required YES

Circuit breaker/Cable section 16A D / 5x2.5mm²

on-ground/in-ground in-ground

Soil quality >20cm Béton C20/25



***Public price Exl. Tax : €15,999**

*Applicable user fees from 01/09/2025 to 31/08/2026

CLAS EQUIPEMENTS
83, chemin de la CROUZA
73800 CHIGNIN
France

Tel : +33 (0) 4 79 72 62 22
Fax :

Monday to Friday - From 8 to 12h
and from 13h30 to 17h30 (16h30 on
Friday)