

## 2 columns post lift high passage 5.10m 400V 4T 4 arms 1.80m

Reference : PE 2250T



<b>Item name</b>	2 columns post lift high passage 5.10m 400V 4T 4 arms 1.80m
<b>Bar code</b>	3701555318103
<b>Text</b>	<p>Electro-hydraulic post lift. Direct push cylinder on cart. Hose and cable routing from the top for optimum working comfort, allowing free access to equipment under the vehicle (cylinders, oil recuperator, etc.), facilitating workshop cleaning. Telescopic arms in symmetrical version with 4 x 1800 mm 3-stage arms.</p>
<b>Product highlight</b>	free circulation between columns
<b>Specifications</b>	<p>Specifications :</p> <ul style="list-style-type: none"><li>- lifting height: 95-1990mm</li><li>- drive power: 2.2kW</li><li>- drive voltage: (3 phases + Neutral) 400V/50Hz</li><li>- screw-adjustable buffers, stroke 70-140mm</li><li>- electrical release of safety catches</li><li>- emergency lowering system in case of power failure</li><li>- intermediate stop at 20cm from the ground for user safety and anti-crushing audible signal</li><li>- engine protection cover</li><li>- door protection on columns</li><li>- 240V electrical socket on electrical box</li><li>- cylinder and cable protection strip included on each column</li></ul>

- supplied with 4 x 70mm risers and supports
- Epoxy paint

**Advice** Installation et mise en service, nous consulter.  
 Mise à disposition d'une nacelle impérative.  
 Dans le cadre de la garantie, l'installation et la mise en service doivent être effectuées par un professionnel.  
 Frais de transport non inclus.

<b>Warranty period</b>	2 years
<b>Power</b>	2200W
<b>Voltage</b>	400V
<b>Length (mm)</b>	3,440 mm
<b>Width</b>	44 mm
<b>Height</b>	5,100 mm
<b>Product weight (kg)</b>	876 kg
<b>Max. height</b>	1,990 mm
<b>Min. height</b>	95 mm
<b>Drive through width</b>	2,600 mm
<b>Maximum load (T)</b>	4 T
<b>Tariff code</b>	Tariff Equipment (TE)
<b>Composition of nomenclature</b>	1 x PE 2200 - 2 columns high passage 400V 4T without arms 1 x PE 2103T - Engine bloc 2 columns post lift 4T 2 x <a href="#">PE 2112 - Pair of arms with block 1.80m and foot protection</a> 1 x <a href="#">PE 2203 - High passage extension and accessories 4T 5m00</a> 2 x <a href="#">SA 3012 - Hv46 hydraulic oil 5l</a>

**Warranty Procedure** INTERVENTION

<b>Customer benefit</b>	Supplied with HV46 hydraulic oil and ground fixing kit
<b>Pneumatic power supply required</b>	NO
<b>Circuit breaker/Cable section</b>	10A D / 5x2.5mm <sup>2</sup>
<b>Soil quality</b>	>20cm Béton C20/25



CLAS EQUIPEMENTS  
83, chemin de la CROUZA  
73800 CHIGNIN  
France

Tel : +33 (0) 4 79 72 62 22  
Fax :

Monday to Friday - From 8 to 12h  
and from 13h30 to 17h30 (16h30 on  
Friday)