2 columns post lift high passage 5.10m 400V 4T 4 arms 1.80m

Reference : PE 2250T



Item name	2 columns post lift high passage 5.10m 400V 4T 4 arms 1.80m
Bar code	3701555318103
Text	Electro-hydraulic post lift. Direct-acting push cylinder mounted on the carriage. Hoses and cables routed from above for optimal working comfort, allowing unobstructed access under the vehicle to equipment (cylinders, waste oil drainers, etc.) and facilitating workshop cleaning. Symmetrical telescopic arms with 4 arms in 3 stages, each 1,800 mm long.
Product highlight	free circulation between columns
Specifications	Specifications: - Lifting height: 95–1,990 mm - Drive power: 2.2 kW - Drive voltage: (3-phase + neutral) 400 V/50 Hz - Adjustable stops on screws, stroke 70–140 mm - Electric release of safety locks - Emergency lowering system in case of power failure - Intermediate stop 20 cm above the floor for user safety and an anti-pinch audible alarm - Motor protective cover - Door protection on the columns - 240V electrical outlet on the control box - Protective strip for the cylinder and cables included on each column - Comes with 4 x 70mm risers and their brackets

	- Epoxy paint finish
Advice	Installation et mise en service, nous consulter. Mise à disposition d'une nacelle impérative. Dans le cadre de la garantie, l'installation et la mise en service doivent être effectuées par un professionnel. Frais de transport non inclus.
Warranty period	2 years
Power	2200W
Voltage	400V
Length (mm)	3,440 mm
Width	44 mm
Height	5,100 mm
Product weight (kg)	876 kg
Max. height	1,990 mm
Min. height	95 mm
Drive through width	2,600 mm
Maximum load (T)	4 T
Tariff code	Tariff Equipment (TE)
Composition of nomenclature	1 x PE 2200 - 2 columns high passage 400V 4T without arms 1 x PE 2103T - Engine bloc 2 columns post lift 4T 2 x PE 2112 - Pair of arms with block 1.80m and foot protection 1 x PE 2203 - High passage extension and accessories 4T 5m00 2 x SA 3012 - Hv46 hydraulic oil 5l
Warranty Procedure	INTERVENTION
Customer benefit	Supplied with HV46 hydraulic oil and ground fixing kit
Pneumatic power supply required	NO
Circuit breaker/Cable section	10A D tetra / 5x2.5mm² (3PH + N + T)
Soil quality	>20cm Béton C20/25



CLAS EQUIPEMENTS
83, chemin de la CROUZA
73800 CHIGNIN
France

Tel : +33 (0) 4 79 72 62 22
Fax :

Monday to Friday - From 8 to 12h and from 13h30 to 17h30 (16h30 on Friday)