

## 2 columns post lift high passage 3.90m 400V 6T 4 articulated arms

Reference : PE 2339T



<b>Item name</b>	2 columns post lift high passage 3.90m 400V 6T 4 articulated arms
<b>Bar code</b>	3701555318035
<b>Text</b>	<p>Particularly suited to repair work on extended utility vehicles, 4x4s, microcars, hybrids and electrics.</p> <p>Electro-hydraulic post lift.</p> <p>Direct push cylinder on carriage.</p> <p>Arms with adjustable joints.</p> <p>Hose and cable routing from the top for optimum working comfort, allowing free access to equipment under the vehicle (cylinders, oil recuperator, battery removal, etc.), facilitating workshop cleaning.</p> <p>Hydraulic power pack: equipped with a position safety device for precise intervention, gearbox assembly, nut alignment, etc.</p> <p>Multiple lifting capacities thanks to 4 multi-adjustable articulated arms.</p> <p>Cylinder and cable protection strip included on each column.</p>
<b>Product highlight</b>	<p>6T capacity</p> <p>Multi-position arm</p>
<b>Specifications</b>	<p>Specifications :</p> <ul style="list-style-type: none"><li>- lifting height: 95-1850mm</li><li>- drive power: 2.2kW</li><li>- drive voltage: (3 phases + Neutral) 400V/50Hz</li><li>- screw-adjustable buffers, stroke 70-140mm</li><li>- electrical release of safety catches</li></ul>

- emergency lowering system in case of power failure
- system synchronization: by cable
- intermediate stop 20cm above ground for user safety and anti-crushing audible signal
- engine protection cover
- door protection on columns
- 240V electrical socket on electrical box
- cylinder and cable protection strip included on each column
- supplied with 4 x 70mm risers and supports
- Epoxy paint

**Advice** Installation et mise en service, nous consulter.  
 Mise à disposition d'une nacelle impérative.  
 Dans le cadre de la garantie, l'installation et la mise en service doivent être effectuées par un professionnel.  
 Frais de transport non inclus.

<b>Warranty period</b>	2 years
<b>Power</b>	2200W
<b>Voltage</b>	400V
<b>Length (mm)</b>	4,000 mm
<b>Height</b>	3,900 mm
<b>Max. height</b>	1,850 mm
<b>Min. height</b>	95 mm
<b>Drive through width</b>	3,190 mm
<b>Maximum load (T)</b>	6 T
<b>Tariff code</b>	Tariff Equipment (TE)
<b>Composition of nomenclature</b>	1 x PE 2340 - 2 columns high passage 400V 6T without arms 1 x PE 2355T - Engine bloc 2 columns post lift 6T 2 x PE 2341 - Pair of articulated arms for 6T 1 x PE 2342 - 2 columns post lift high passage 6T 2 x <a href="#">SA 3012 - Hv46 hydraulic oil 5l</a>

**Warranty Procedure** INTERVENTION

<b>Customer benefit</b>	Supplied with HV46 hydraulic oil and ground fixing kit
<b>Pneumatic power supply required</b>	NO
<b>Circuit breaker/Cable section</b>	10A D / 5x2.5mm <sup>2</sup>
<b>Soil quality</b>	>20cm Béton C20/25

**2**  
WARRANTY

**2200**  
**W**

  
**400V**



TE

**\*Public price Exl. Tax : €9,999**

\*Applicable user fees from 01/09/2025 to 31/08/2026

CLAS EQUIPEMENTS  
83, chemin de la CROUZA  
73800 CHIGNIN  
France

Tel : +33 (0) 4 79 72 62 22  
Fax :

Monday to Friday - From 8 to 12h  
and from 13h30 to 17h30 (16h30 on  
Friday)