

## 2 columns symetric post lift with basement 400V 4T 4 arms 1.80m

Reference : PE 2106T



<b>Item name</b>	2 columns symetric post lift with basement 400V 4T 4 arms 1.80m
<b>Bar code</b>	3701555318158
<b>Text</b>	<p>Lift designed to facilitate column installation and alignment thanks to its 40mm-thick base.</p> <p>With the PE 2101 option, it can be used for screeds that don't meet the minimum thickness requirement of 200mm (can cover up to 150mm), or with slight flatness problems.</p> <p>Electro-hydraulic post lift.</p> <p>Pusher cylinder on cable, carriage pulled by chain.</p> <p>Telescopic arms in symmetrical version with 4 x 1800mm 3-stage arms.</p>
<b>Product highlight</b>	Low-thickness passage
<b>Specifications</b>	<p>Specifications :</p> <ul style="list-style-type: none"><li>- lifting height: 100-2100mm</li><li>- drive power: 2.2kW</li><li>- drive voltage: (3 phases + Neutral) 400V/50Hz</li><li>- screw-adjustable buffers, stroke 70-140mm</li><li>- automatic release of safety catches</li><li>- emergency lowering system in case of power failure</li><li>- system synchronization: by cable</li><li>- intermediate stop 20cm above ground for user safety and anti-crushing audible signal</li><li>- engine protection cover</li><li>- door protection on columns</li><li>- 230V electrical socket on electrical box</li></ul>

- protective strip for cylinder, chain and cables included on each column
- supplied with 4 x 70mm risers and brackets
- Epoxy paint

**Advice** Installation et mise en service, nous consulter.  
 Dans le cadre de la garantie, l'installation et la mise en service doivent être effectuées par un professionnel.  
 Frais de transport non inclus.

**Warranty period** 2 years

**Power** 2200W

**Voltage** 400V

**Length (mm)** 3,440 mm

**Width** 44 mm

**Height** 2,965 mm

**Product weight (kg)** 823 kg

**Max. height** 2,100 mm

**Min. height** 100 mm

**Drive through width** 2,460 mm

**Tariff code** Tariff Equipment (TE)

**Composition of nomenclature** 1 x PE 2102 - 2 columns with basement 400V 4T without arms  
 1 x PE 2103T - Engine bloc 2 columns post lift 4T  
 1 x PE 2104 - 2 columns post lift with basement accessories 4T  
 2 x [PE 2112 - Pair of arms with block 1.80m and foot protection](#)  
 2 x [SA 3012 - Hv46 hydraulic oil 5l](#)  
 1 x PE 2117 - 2 columns post lift base 4T low passage

**Warranty Procedure** INTERVENTION

**Customer benefit** Supplied with HV46 hydraulic oil and ground fixing kit

**Pneumatic power supply required** NO

**Circuit breaker/Cable section** 10A D / 5x2.5mm<sup>2</sup>

**Soil quality** >20cm Béton C20/25



CLAS EQUIPEMENTS  
83, chemin de la CROUZA  
73800 CHIGNIN  
France

Tel : +33 (0) 4 79 72 62 22  
Fax :

Monday to Friday - From 8 to 12h  
and from 13h30 to 17h30 (16h30 on  
Friday)