

2 columns symetric post lift with basement 400V 4T 4 arms 1.80m

Reference : PE 2106T



Item name	2 columns symetric post lift with basement 400V 4T 4 arms 1.80m
Bar code	3701555318158
Text	<p>Lift designed to facilitate column installation and alignment thanks to its 40mm-thick base.</p> <p>With the PE 2101 option, it can be used for screeds that don't meet the minimum thickness requirement of 200mm (can cover up to 150mm), or with slight flatness problems.</p> <p>Electro-hydraulic post lift.</p> <p>Pusher cylinder on cable, carriage pulled by chain.</p> <p>Telescopic arms in symmetrical version with 4 x 1800mm 3-stage arms.</p>
Product highlight	Low-thickness passage
Specifications	<p>Specifications :</p> <ul style="list-style-type: none">- lifting height: 100-2100mm- drive power: 2.2kW- drive voltage: (3 phases + Neutral) 400V/50Hz- screw-adjustable buffers, stroke 70-140mm- automatic release of safety catches- emergency lowering system in case of power failure- system synchronization: by cable- intermediate stop 20cm above ground for user safety and anti-crushing audible signal- engine protection cover- door protection on columns- 230V electrical socket on electrical box

- protective strip for cylinder, chain and cables included on each column
- supplied with 4 x 70mm risers and brackets
- Epoxy paint

Advice Installation et mise en service, nous consulter.
 Dans le cadre de la garantie, l'installation et la mise en service doivent être effectuées par un professionnel.
 Frais de transport non inclus.

Warranty period 2 years

Power 2200W

Voltage 400V

Length (mm) 3,440 mm

Width 44 mm

Height 2,965 mm

Product weight (kg) 823 kg

Max. height 2,100 mm

Min. height 100 mm

Drive through width 2,460 mm

Tariff code Tariff Equipment (TE)

Composition of nomenclature 1 x PE 2102 - 2 columns with basement 400V 4T without arms
 1 x PE 2103T - Engine bloc 2 columns post lift 4T
 1 x PE 2104 - 2 columns post lift with basement accessories 4T
 2 x [PE 2112 - Pair of arms with block 1.80m and foot protection](#)
 2 x [SA 3012 - Hv46 hydraulic oil 5l](#)
 1 x PE 2117 - 2 columns post lift base 4T low passage

Warranty Procedure INTERVENTION

Customer benefit Supplied with HV46 hydraulic oil and ground fixing kit

Pneumatic power supply required NO

Circuit breaker/Cable section 10A D / 5x2.5mm²

Soil quality >20cm Béton C20/25



***Public price Exl. Tax : €4,399**

*Applicable user fees from 01/09/2025 to 31/08/2026

CLAS EQUIPEMENTS
83, chemin de la CROUZA
73800 CHIGNIN
France

Tel : +33 (0) 4 79 72 62 22
Fax :

Monday to Friday - From 8 to 12h
and from 13h30 to 17h30 (16h30 on
Friday)