2 columns symetric post lift with basement 400V 4T 4 arms 1.80m

Reference : PE 2106T



Item name	2 columns symetric post lift with basement 400V 4T 4 arms 1.80m
Bar code	3701555318158
Text	Lift designed to facilitate column installation and alignment thanks to its 40mm-thick base. With the PE 2101 option, it can be used for screeds that don't meet the minimum thickness requirement of 200mm (can cover up to 150mm), or with slight flatness problems. Electro-hydraulic post lift. Pusher cylinder on cable, carriage pulled by chain. Telescopic arms in symmetrical version with 4 x 1800mm 3-stage arms.
Product highlight	Low-thickness passage
Specifications	Specifications: - lifting height: 100-2100mm - drive power: 2.2kW - drive voltage: (3 phases + Neutral) 400V/50Hz - screw-adjustable buffers, stroke 70-140mm - automatic release of safety catches - emergency lowering system in case of power failure - system synchronization: by cable - intermediate stop 20cm above ground for user safety and anti-crushing audible signal - engine protection cover - door protection on columns - 230V electrical socket on electrical box

	- protective strip for cylinder, chain and cables included on each column - supplied with 4 x 70mm risers and brackets - Epoxy paint
Advice	Installation et mise en service, nous consulter. Dans le cadre de la garantie, l'installation et la mise en service doivent être effectuées par un professionnel. Frais de transport non inclus.
Warranty period	2 years
Power	2200W
Voltage	400V
Length (mm)	3,440 mm
Width	44 mm
Height	2,965 mm
Product weight (kg)	823 kg
Max. height	2,100 mm
Min. height	100 mm
Drive through width	2,460 mm
Tariff code	Tariff Equipment (TE)
Composition of nomenclature	1 x PE 2102 - 2 columns with basement 400V 4T without arms 1 x PE 2103T - Engine bloc 2 columns post lift 4T 1 x PE 2104 - 2 columns post lift with basement accessories 4T 2 x PE 2112 - Pair of arms with block 1.80m and foot protection 2 x SA 3012 - Hv46 hydraulic oil 5l 1 x PE 2117 - 2 columns post lift base 4T low passage
Warranty Procedure	INTERVENTION
Customer benefit	Supplied with HV46 hydraulic oil and ground fixing kit
Pneumatic power supply required	NO
Circuit breaker/Cable section	10A D tetra / 5x2.5mm² (3PH + N + T)
Soil quality	>20cm Béton C20/25



***Public price Exl. Tax : €4,399**

*Applicable user fees from 01/09/2026 to 31/08/2027

CLAS EQUIPEMENTS
83, chemin de la CROUZA
73800 CHIGNIN
France

Tel : +33 (0) 4 79 72 62 22
Fax :

Monday to Friday - From 8 to 12h and from 13h30 to 17h30 (16h30 on Friday)