

2 columns post lift high passage 3.90m 400V 4T 4 arms 1.50m

Reference : PE 2238T



Item name	2 columns post lift high passage 3.90m 400V 4T 4 arms 1.50m
Bar code	3701555318011
Text	<p>Electro-hydraulic post lift. Direct push cylinder on cart. Hose and cable routing from the top for optimum working comfort, allowing free access to equipment under the vehicle (cylinders, oil recuperator, battery removal, etc.), facilitating workshop cleaning. Telescopic arms in symmetrical version with 4 x 1500 mm 3-stage arms.</p>
Product highlight	Free movement between columns
Specifications	<p>Specifications :</p> <ul style="list-style-type: none">- lifting height: 950-1990mm- drive power: 2.2kW- drive voltage: (3 phases + Neutral) 400V/50Hz- screw-adjustable buffers, stroke 70-140mm- electrical release of safety catches- emergency lowering system in case of power failure- system synchronization: by cable- intermediate stop 20cm above ground for user safety and anti-crushing audible signal- engine protection cover- door protection on columns- 240V electrical socket on electrical box- cylinder and cable protection strip included on each column

- supplied with 4 x 70mm risers and supports
- Epoxy paint

Advice Installation et mise en service, nous consulter.
 Mise à disposition d'une nacelle impérative.
 Dans le cadre de la garantie, l'installation et la mise en service doivent être effectuées par un professionnel.
 Frais de transport non inclus.

Warranty period	2 years
Power	2200W
Voltage	400V
Length (mm)	3,440 mm
Width	44 mm
Height	3,900 mm
Product weight (kg)	792 kg
Max. height	1,990 mm
Min. height	950 mm
Drive through width	2,600 mm
Maximum load (T)	4 T
Tariff code	Tariff Equipment (TE)
Composition of nomenclature	1 x PE 2200 - 2 columns high passage 400V 4T without arms 1 x PE 2103T - Engine bloc 2 columns post lift 4T 1 x PE 2204 - 2 columns post lift high passage 4T 3m80 2 x PE 2111 - Pair of arms with block 1.50m and foot protection 2 x SA 3012 - Hv46 hydraulic oil 5l

Warranty Procedure INTERVENTION

Customer benefit	Supplied with HV46 hydraulic oil and ground fixing kit
Pneumatic power supply required	NO
Circuit breaker/Cable section	10A D / 5x2.5mm ²
Soil quality	>20cm Béton C20/25



CLAS EQUIPEMENTS
83, chemin de la CROUZA
73800 CHIGNIN
France

Tel : +33 (0) 4 79 72 62 22
Fax :

Monday to Friday - From 8 to 12h
and from 13h30 to 17h30 (16h30 on
Friday)