2 columns post lift high passage 3.90m 400V 4T 4 arms 1.50m

Reference : PE 2238T



Item name	2 columns post lift high passage 3.90m 400V 4T 4 arms 1.50m
Bar code	3701555318011
Text	Electro-hydraulic post lift. Direct-acting lift cylinder mounted on the carriage. Hoses and cables routed overhead for optimal working comfort, allowing unobstructed access under the vehicle for equipment (jacks, waste oil drainers, battery removal, etc.) and facilitating workshop cleaning. Symmetrical telescoping arms with 4 arms in 3 stages, each 1,500 mm long.
Product highlight	Free movement between columns
Specifications	Specifications: - Lifting height: 950–1990 mm - Drive power: 2.2 kW - Drive voltage: (3-phase + neutral) 400 V/50 Hz - Adjustable stops on screws, travel: 70–140 mm - Electric release of safety locks - Emergency lowering system in case of power failure - System synchronization: via cable - Intermediate stop 20 cm above the floor for user safety and an anti-pinch audible alarm - Motor protective cover - Door protection on the columns - 240V electrical outlet on the control box - Protective strip for the cylinder and cables included on each column

	- Comes with 4 x 70mm risers and their brackets - Epoxy paint finish
Advice	Installation et mise en service, nous consulter. Mise à disposition d'une nacelle impérative. Dans le cadre de la garantie, l'installation et la mise en service doivent être effectuées par un professionnel. Frais de transport non inclus.
Warranty period	2 years
Power	2200W
Voltage	400V
Length (mm)	3,440 mm
Width	44 mm
Height	3,900 mm
Product weight (kg)	792 kg
Max. height	1,990 mm
Min. height	950 mm
Drive through width	2,600 mm
Maximum load (T)	4 T
Tariff code	Tariff Equipment (TE)
Composition of nomenclature	1 x PE 2200 - 2 columns high passage 400V 4T without arms 1 x PE 2103T - Engine bloc 2 columns post lift 4T 1 x PE 2204 - 2 columns post lift high passage 4T 3m80 2 x PE 2111 - Pair of arms with block 1.50m and foot protection 2 x SA 3012 - Hv46 hydraulic oil 5l
Warranty Procedure	INTERVENTION
Customer benefit	Supplied with HV46 hydraulic oil and ground fixing kit
Pneumatic power supply required	NO
Circuit breaker/Cable section	10A D tetra / 5x2.5mm² (3PH + N + T)
Soil quality	>20cm Béton C20/25



CLAS EQUIPEMENTS
83, chemin de la CROUZA
73800 CHIGNIN
France

Tel : +33 (0) 4 79 72 62 22
Fax :

Monday to Friday - From 8 to 12h and from 13h30 to 17h30 (16h30 on Friday)